

# Des-Case FlowGuard™

Fluid Handling & Filtration

## QUOTE FORM

Please complete this form and fax to +1 905 569 8605 to receive a detailed quote on the system requested.

**NOTE:** To receive pricing on-line from the Lubrigard Web site first register a new account and then browse products from the Products link.



### CONTACT INFORMATION

Would you like a representative to contact you?  Yes  No

**Company Name** \_\_\_\_\_

Contact Name \_\_\_\_\_

Contact Phone \_\_\_\_\_ Fax \_\_\_\_\_


E-Mail Address \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State/Prov \_\_\_\_\_

Country \_\_\_\_\_ Zip/Postal \_\_\_\_\_

### PLEASE QUOTE ON THE FOLLOWING DES-CASE FILTER CART



Code	Pump*
02E	2 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 680 cSt)
05E	5 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 220 cSt)
10E	10 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 68 cSt)
20E†	20 GPM / 1.5 HP Electric 115 VAC (Viscosity ≤ 68 cSt)
02F	2 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 460 cSt)
05F	5 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 220 cSt)
10F	10 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 68 cSt)
20F†	20 GPM / 1.5 HP Electric 230 VAC (Viscosity ≤ 68 cSt)
02A	2 GPM / 1.5 HP Air (Viscosity ≤ 680 cSt)
08A	8 GPM / 1.5 HP Air (Viscosity ≤ 68 cSt)

Code	Drain / Fill Connectors*
F3**	½" Flush Face
F5	¾" Flush Face
F7	1" Flush Face
A3**	½" ISO A
A5	¾" ISO A
A7	1" ISO A
B3**	½" ISO B
B5	¾" ISO B
B7	1" ISO B
N3**	½" Threaded End
N5	¾" Threaded End
N7	1" Threaded End
W	Wand

Code	Filter A / Filter B
A	3µm
B	6µm
C	12µm
D	25µm
J	Water Removal

Code	Bypass
0	No Bypass
1	Filter Bypass

Code	Sample Port
0	None
1	Standard
2	High-Viscosity

Code	Electric Cord
0	None (air pump)
1	25 foot cord
2**	25' with reel

Code	Relief Valve*
0	None
1	Relief Valve

\* This safety relief valve prevents the pump pressure from surpassing 65 PSI.

Code	Color
1	Brushed Aluminum
2	Black
3	White
4	Blue
5	Red
6	Yellow

† Due to amperage draw, the 230 VAC (20F) is favored when selecting a 20GPM system.

• Performance will vary depending on temperature, filter combination, bypass options, hose sizes, connectors, and fluid type.

\* - All are coupler ends (female)  
\*\* - Not suitable for a 20 GPM pump

# Des-Case FlowGuard™

Fluid Handling & Filtration

## QUOTE FORM

Please complete this form and fax to +1 905 569 8605 to receive a detailed quote on the system requested.

**NOTE:** To receive pricing on-line from the Lubrigard Web site first register a new account and then browse products from the Products link.



### CONTACT INFORMATION

Would you like a representative to contact you?  Yes  No

**Company Name** \_\_\_\_\_

Contact Name \_\_\_\_\_

Contact Phone \_\_\_\_\_ Fax \_\_\_\_\_

E-Mail Address \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State/Prov \_\_\_\_\_

Country \_\_\_\_\_ Zip/Postal \_\_\_\_\_

### PLEASE QUOTE ON THE FOLLOWING DES-CASE DRUM FILTER CART



Code	Pump*
02E	2 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 680 cSt)
02F	2 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 460 cSt)
02A	2 GPM / 1.5 HP Air (Viscosity ≤ 680 cSt)

\*Performance will vary depending on temperature, filter combination, bypass options, hose sizes, connectors, and fluid type.

Code	Drain / Fill Connectors*
F3	½" Flush Face
F5	¾" Flush Face
F7	1" Flush Face
A3	½" ISO A
A5	¾" ISO A
A7	1" ISO A
B3	½" ISO B
B5	¾" ISO B
B7	1" ISO B
N3	½" Threaded End
N5	¾" Threaded End
N7	1" Threaded End
W	Wand

\* - All are coupler ends (female)

Code	Filter A / Filter B
A	3µm
B	6µm
C	12µm
D	25µm
J	Water Removal

Code	Bypass
0	No Bypass
1	Filter Bypass

Code	Sample Port
0	None
1	Standard
2	High-Viscosity

Code	Color
1	Brushed Aluminum
2	Black
3	White
4	Blue
5	Red
6	Yellow

# Des-Case FlowGuard™

Fluid Handling & Filtration

## QUOTE FORM

Please complete this form and fax to +1 905 569 8605 to receive a detailed quote on the system requested.

**NOTE:** To receive pricing on-line from the Lubrigard Web site first register a new account and then browse products from the Products link.

### CONTACT INFORMATION

Would you like a representative to contact you?  Yes  No

**Company Name** \_\_\_\_\_

Contact Name \_\_\_\_\_

Contact Phone \_\_\_\_\_ Fax \_\_\_\_\_

E-Mail Address \_\_\_\_\_


Address \_\_\_\_\_

City \_\_\_\_\_ State/Prov \_\_\_\_\_

Country \_\_\_\_\_ Zip/Postal \_\_\_\_\_



### PLEASE QUOTE ON THE FOLLOWING DES-CASE DRUM TOPPER



Code	Pump*
01E	1 GPM / .25 HP Electric 115 VAC, 60hz, 1725 rpms, 5 amps
01F	1 GPM / .25 HP Electric 230 VAC, 60hz, 1725 rpms, 2.5 amps
01G	.75 GPM / .25 HP Electric 110 VAC, 50hz, 1425 rpms, 5.4 amps
01H	.75 GPM / .25 HP Electric 110 VAC, 50hz, 1425 rpms, 5.4 amps
03E	3.5 GPM / .25 HP Electric 115 VAC, 60hz, 1725 rpms, 5 amps
03F	.75 GPM / .25 HP Electric 230 VAC, 60hz, 1725 rpms, 2.5 amps
03G	2.75 GPM / .25 HP Electric 110 VAC, 50hz, 1425 rpms, 5.4 amps
03H	2.75 GPM / .25 HP Electric 220 VAC, 50hz, 1425 rpms, 2.7 amps
02A	2 GPM / 1.7 HP air, 0-3000 rpms
08A	8 GPM / 1.7 HP air, 0-3000 rpms

Code	Drain / Fill Connectors*
F3	½" Flush Face
F5	¾" Flush Face
F7	1" Flush Face
A3	½" ISO A
A5	¾" ISO A
A7	1" ISO A
B3	½" ISO B
B5	¾" ISO B
B7	1" ISO B
N3	½" Threaded End
N5	¾" Threaded End
N7	1" Threaded End
W	Wand

Code	Filter A / Filter B
K	3µm
L	6µm
M	12µm
W	Water Removal
0	None

Code	Bypass
0	No Bypass
1	Filter Bypass

Code	Sample Port
0	None
1	Standard
2	High-Viscosity

Code	Color
1	Brushed Aluminum
2	Black
3	White
4	Blue
5	Red
6	Yellow

\*Performance will vary depending on temperature, filter combination, bypass options, hose sizes, connectors, and fluid type.

\* - All are coupler ends (female)

# Des-Case FlowGuard™

Fluid Handling & Filtration

## QUOTE FORM

Please complete this form and fax to +1 905 569 8605 to receive a detailed quote on the system requested.

**NOTE:** To receive pricing on-line from the Lubrigard Web site first register a new account and then browse products from the Products link.



### CONTACT INFORMATION

Would you like a representative to contact you?  Yes  No

**Company Name** \_\_\_\_\_

Contact Name \_\_\_\_\_

Contact Phone \_\_\_\_\_ Fax \_\_\_\_\_

E-Mail Address \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State/Prov \_\_\_\_\_

Country \_\_\_\_\_ Zip/Postal \_\_\_\_\_

### PLEASE QUOTE ON THE FOLLOWING DES-CASE PANEL UNIT



Code	Pump*
02E	2 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 680 cSt)
05E	5 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 220 cSt)
10E	10 GPM / 1 HP Electric 115 VAC (Viscosity ≤ 68 cSt)
02F	<b>2 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 460 cSt)</b>
05F	5 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 220 cSt)
10F	10 GPM / 1 HP Electric 230 VAC (Viscosity ≤ 68 cSt)
02A	2 GPM / 1.5 HP Air (Viscosity ≤ 680 cSt)
08A	8 GPM / 1.5 HP Air (Viscosity ≤ 68 cSt)

Code	Filter A / Filter B
A	3µm
B	6µm
C	12µm
D	25µm
J	Water Removal

Code	Sample Port
0	None
1	Standard
2	High-Viscosity

Code	Relief Valve*
0	None
1	Relief Valve

\* This safety relief valve prevents the pump pressure from surpassing 65 PSI.

Code	Oil Cooler
0	None
1	Oil Cooler

Code	Temp Gauge
0	None
1	Temp Gauge

Code	Bypass
0	No Bypass
1	Filter Bypass

Code	Color
1	Brushed Aluminum
2	Black
3	White
4	Blue
5	Red
6	Yellow

\*Performance will vary depending on temperature, filter combination, bypass options, hose sizes, connectors, and fluid type.

# Des-Case FlowGuard™

Fluid Handling & Filtration

## QUOTE FORM

Please complete this form and fax to +1 905 569 8605 to receive a detailed quote on the system requested.

**NOTE:** To receive pricing on-line from the Lubrigard Web site first register a new account and then browse products from the Products link.



### CONTACT INFORMATION

Would you like a representative to contact you?  Yes  No

**Company Name** \_\_\_\_\_

Contact Name \_\_\_\_\_

Contact Phone \_\_\_\_\_ Fax \_\_\_\_\_


E-Mail Address \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State/Prov \_\_\_\_\_

Country \_\_\_\_\_ Zip/Postal \_\_\_\_\_

### PLEASE QUOTE ON THE FOLLOWING DES-CASE ADAPTER KIT



Code	Adapter Type
HA	Hydraulic Adapter (6-Hole Flange)
DA	Drum Adapter (2" NPT)
GA	Gearbox Adapter (3/4" NPT)
TA	Tote Adapter (2" NPT)

Code	Drain / Fill Connectors*
F3**	1/2" Flush Face
F5	3/4" Flush Face
F7	1" Flush Face
A3**	1/2" ISO A
A5	3/4" ISO A
A7	1" ISO A
B3**	1/2" ISO B
B5	3/4" ISO B
B7	1" ISO B

\* - All are plug ends (male)  
 \*\* - Not for greater than 10 GPM.

Code	Fill Tube Length
XX	Enter 2 digits (e.g. 08 for 8")
Recommended Lengths	
06	Drum (DA)
02	Gearbox (GA)
02	Tote (TA)

Code	Sample Port*
0	None
1	Standard

\* Enter 0 for the Drum, Gearbox, and Tote Adapters.

Code	Drain Tube Length
XX	Enter 2 digits (e.g. 08 for 8")
Recommended Lengths	
35	Drum (DA)
00	Gearbox (GA)
00	Tote (TA)

\* Enter 00 if customizing a Gearbox or Tote Adapter.

Code	Air Breather
02*	3µm desiccant breather [DC-2]
03**	3µm desiccant breather [DC-2]
04**	3µm desiccant breather [DC-2]
25	1µm non-desiccant breather [DC-SB-25]
35	1µm non-desiccant breather [DC-SB-35]
H8***	3µm desiccant breather [DC-2]

\* - For Drum (DA) Adapter  
 \*\* - For Hydraulic Adapter (HA)  
 \*\*\* - For Gearbox (GA) Adapter