

**Polytank Lubricant Storage System**  
Improve your Lubrication Procedures

# Lubricant Storage

Polytank Lubricant Storage System PROVIDES YOU WITH THE LATEST IN LUBRICANT STORAGE TECHNOLOGY FEATURING BUILT-IN CONTAMINATION CONTROL, EASY SET-UP, DEPLOYMENT, AND EASE OF USE.



## BENEFITS

### Improved Lubricant Storage

Polytank Lubricant Storage System combines filtration, storage and breather technologies all in one small package designed to keep your lubricants clean during storage, before they enter your equipment.

### All-in-One Package

Polytank Lubricant Storage System combines easy storage with solid contamination control practices. A filtration system allows for pre-filtering of fluids during fill and filtration of lubricants while in the storage system. Air pumps provide segregated fill and dispensing operations at all times. Segregated hoses are equipped with quick disconnects for easy and clean fill and dispensing tasks. Integrated desiccant air breathers ensure that oil is kept particulate and moisture free during storage.

### Efficient Use of Space

Polytank Lubricant Storage System features sturdy stackable 70 gallon Poly Tanks that are easy to set-up and free up valuable floor space. No assembly is required aside from stacking the units and mounting the steel frame.

### The Latest in Fluid Handling

For ease of set-up and use, compact storage design, and built-in features, the Polytank Lubricant Storage System is the most economical system on the market today.

## OVERVIEW

- Single stage filtration ensures optimal lubricant cleanliness.
- Customizable system allows for use with many lubricant types.
- Dedicated 1:1 or 3:1 air pumps on each tank eliminates cross-contamination from using common pumps, motors or filters.
- 70 Gallon and 145 Gallon tank configurations available. Stackable design.
- Easy and quick installation.



PROACTIVE LUBRICATION MANAGEMENT



# Polytank Lubricant Storage System

Improve your Lubrication Procedures

## FEATURES

### Polytank

Standard tank size - 70 and 145 Gallon.  
Optional 870L/220Gal available.

Eliminates the need for expensive steel tank upgrades. Upgrades include high-viscosity oil tank or stainless steel upgrades.

### 3-Way Valve/Filter Arrangement

- \* Allows for oil to be filtered when transferring.
- \* Filters the oil in the polytank.
- \* Filters when dispensing.

### Air Pumps

Air pumps offers you more flexibility when using high-viscosity oil and also eliminates expensive motor upgrades in explosion proof requirements and applications.

### Filtration

Filtration system offers a wide variety from low micron to water removal filters.

### Breather

Des-Case desiccant breathers offer complete contamination control.

These filters prevent moisture and dirt from entering the polytanks.

### Suction and Dispensing Hoses

Each hose is equipped with quick-connects for fast hook-ups. Hose sizes and a choice of dispensing handles are available.



## STANDARD STORAGE SYSTEMS



Polytank Pod System  
3 containers stacked  
[PTPOD370]

Number of Containers: 3  
Oil Volume per Tank: 265 liters (70 US gallons)  
Tank size: 32" W x 32" D x 20" H  
Spill Containment size: 43" W x 48" L x 6" H  
Pod Height: 88"  
Pod Width: 43"



Polytank Pod System  
1 x 70 Gal & 1 x 145 Gal containers stacked  
[PTPOD70145]

Number of Containers: 2  
Oil Volume per Tank: 265 liters (70 US gallons)  
Oil Volume per Tank: 550 liters (145 US gallons)  
Tank size: 32" W x 32" D x 20" H  
Tank size: 32" W x 32" D x 40" H  
Spill Containment size: 43" W x 48" L x 6" H  
Pod Height: 88"  
Pod Width: 43"



Polytank Pod System  
3 X 70 Gallon (265 L) Poly Container System  
with hose reel  
[PTPOD370-30HR]

Number of Containers: 3  
Oil Volume per Tank: 265 liters (70 US gallons)  
Tank size: 32" W x 32" D x 20" H  
Spill Containment size: 43" W x 48" L x 6" H  
Hose Reel with 1/2 hose - 30ft long  
Dispensing handles(standard, metered or preset)  
Pod Height: 108"  
Pod Width: 43"



PROACTIVE LUBRICATION MANAGEMENT

©2003-2011 Lubrigard Ltd. All Rights Reserved. All illustrations, photographs and specifications within this literature are based on the latest product information. All information contained on this literature is intended for the Canadian market only. The information contained on this literature may be changed at any time without prior notification or obligation. Lubrigard Ltd. makes no representations as to the accuracy of this information. See actual product at your Lubrigard Dealership for complete accuracy. Lubrigard Ltd. reserves the right to make changes at any time, without notice, in prices, colours, materials, equipment, specifications and models, and to discontinue models or equipment. For information on additional options and accessories, contact your Lubrigard Dealership. All product brand names are Lubrigard trademarks.

LG-POLYTANK-2011-03-08

Lubrigard Ltd. C8-1175 Appleby Line, Burlington, ON, L7L 5H9 Tel 905-569-8600 Toll-free 800-268-2131 Fax 905-569-8605 URL <http://www.lubrigard.com>