



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
813044
Component
Diesel Engine
Fluid
PETRO CANADA 10W30 (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PC0082005	PC0081903	PC0075464
Sample Date		Client Info		08 Jan 2024	04 Dec 2023	11 Jul 2023
Machine Age	kms	Client Info		30205	28006	21039
Oil Age	kms	Client Info		0	0	0
Filter Age	kms	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Les taux de métaux sont typiques pour la période de rodage d'un nouveau composant.

Iron	ppm	ASTM D5185(m)	>80	11	29	21
Chromium	ppm	ASTM D5185(m)	>5	<1	1	1
Nickel	ppm	ASTM D5185(m)	>2	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>3	0	<1	0
Aluminum	ppm	ASTM D5185(m)	>30	3	5	4
Lead	ppm	ASTM D5185(m)	>30	0	0	0
Copper	ppm	ASTM D5185(m)	>150	1	4	4
Tin	ppm	ASTM D5185(m)	>5	0	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>20	3	3	3
Potassium	ppm	ASTM D5185(m)	>20	4	11	7
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>3	0.1	0.4	0.3
Nitration	Abs/cm	ASTM D7624*	>20	6.3	9.5	8.7
Sulfation	Abs/.1mm	ASTM D7415*	>30	18.7	20.9	20.7
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

L'état de l'huile est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		<1	2	2
Boron	ppm	ASTM D5185(m)		9	6	5
Barium	ppm	ASTM D5185(m)		0	<1	0
Molybdenum	ppm	ASTM D5185(m)		59	62	59
Manganese	ppm	ASTM D5185(m)		0	<1	<1
Magnesium	ppm	ASTM D5185(m)		938	980	972
Calcium	ppm	ASTM D5185(m)		1034	1098	1058
Phosphorus	ppm	ASTM D5185(m)		1002	1014	1079
Zinc	ppm	ASTM D5185(m)		1158	1219	1225
Sulfur	ppm	ASTM D5185(m)		2712	2528	2499
Oxidation	Abs/.1mm	ASTM D7414*	>25	14.0	17.3	16.3
Visc @ 40°C	cSt	ASTM D7279(m)		71.8	72.8	71.4
Visc @ 100°C	cSt	ASTM D7279(m)		11.1	11.2	10.9
Viscosity Index (VI)	Scale	ASTM D2270*		145	145	142



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 GFL Environmental - 737 - Quebec City Hauling
Sample No. : PC0082005 **Received** : 10 Jan 2024 6205 Boul. Wilfrid Hamel,
Lab Number : 02607707 **Diagnosed** : 10 Jan 2024 Quebec City, QC
Unique Number : 5708793 **Diagnostician** : Wes Davis CA G2E 5G8
Test Package : MOB 1 (Additional Tests: KV40, VI) Contact: Michel .
 mmorissette@matrec.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

F: x: