



Machine Id  
**901141**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

### RECOMMENDATION

Resample at the next service interval to monitor. ( Customer Sample Comment: Not sure if this is a resample. Last recorded PM December 22 at 11602 Hrs. but cannot locate records in Webcheck )

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0097589</b>	GFL0097548	GFL0088957
Sample Date		Client Info		<b>09 Jan 2024</b>	30 Oct 2023	01 Sep 2023
Machine Age	hrs	Client Info		<b>11720</b>	11003	10548
Oil Age	hrs	Client Info		<b>118</b>	10548	568
Filter Age	hrs	Client Info		<b>118</b>	10548	568
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>120	<b>2</b>	4	5
Chromium	ppm	ASTM D5185(m)	>20	<b>0</b>	0	<1
Nickel	ppm	ASTM D5185(m)	>5	<b>0</b>	0	0
Titanium	ppm	ASTM D5185(m)	>2	<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>2	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185(m)	>20	<b>1</b>	1	<1
Lead	ppm	ASTM D5185(m)	>40	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185(m)	>330	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185(m)	>15	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0

### CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>25	<b>2</b>	3	3
Potassium	ppm	ASTM D5185(m)	>20	<b>4</b>	<1	<1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	ASTM D7844*	>4	<b>0</b>	0.2	0.3
Nitration	Abs/cm	ASTM D7624*	>20	<b>5.2</b>	6.5	7.6
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>17.9</b>	18.1	20.0
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<b>&lt;1</b>	3	3
Boron	ppm	ASTM D5185(m)	0	<b>4</b>	6	4
Barium	ppm	ASTM D5185(m)	0	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185(m)	60	<b>55</b>	67	59
Manganese	ppm	ASTM D5185(m)	0	<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185(m)	1010	<b>929</b>	1087	967
Calcium	ppm	ASTM D5185(m)	1070	<b>1035</b>	1208	1055
Phosphorus	ppm	ASTM D5185(m)	1150	<b>1009</b>	1111	1094
Zinc	ppm	ASTM D5185(m)	1270	<b>1126</b>	1341	1182
Sulfur	ppm	ASTM D5185(m)	2060	<b>2684</b>	2836	2540
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>13.4</b>	13.8	14.8
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	<b>14.2</b>	13.9	13.8



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0097589 **Received** : 11 Jan 2024  
**Lab Number** : 02608145 **Diagnosed** : 12 Jan 2024  
**Unique Number** : 5709231 **Diagnostician** : Kevin Marson  
**Test Package** : MOB 1

**GFL Environmental - 216**  
 15 Bermondsey Road  
 Toronto, ON  
 CA M4B 1Y9  
 Contact: Tom Hatzioannidis  
 thatzioannidis@gflenv.com  
 T: (416)678-9340  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.