



Machine Id
801038
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (23 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0107148	GFL0107145	GFL0094199
Sample Date		Client Info		11 Jan 2024	09 Jan 2024	13 Oct 2023
Machine Age	hrs	Client Info		731003	12752	12224
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	Changed	Changed
Filter Changed		Client Info		Not Chngd	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>80	7	27	32
Chromium	ppm	ASTM D5185(m)	>5	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>3	0	0	<1
Aluminum	ppm	ASTM D5185(m)	>30	2	5	4
Lead	ppm	ASTM D5185(m)	>30	<1	<1	<1
Copper	ppm	ASTM D5185(m)	>150	<1	1	2
Tin	ppm	ASTM D5185(m)	>5	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	VLITE	---	---

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	5	7	9
Potassium	ppm	ASTM D5185(m)	>20	2	▲ 7	3
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	▲ 0.015	NEG
Soot %	%	ASTM D7844*	>3	0	0.6	0.7
Nitration	Abs/cm	ASTM D7624*	>20	5.4	10.4	10.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	18.6	22.5	21.7
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		19	▲ 39	10
Boron	ppm	ASTM D5185(m)	0	12	18	5
Barium	ppm	ASTM D5185(m)	0	0	0	<1
Molybdenum	ppm	ASTM D5185(m)	60	59	63	64
Manganese	ppm	ASTM D5185(m)	0	0	0	0
Magnesium	ppm	ASTM D5185(m)	1010	931	864	993
Calcium	ppm	ASTM D5185(m)	1070	1026	1129	1108
Phosphorus	ppm	ASTM D5185(m)	1150	1008	980	985
Zinc	ppm	ASTM D5185(m)	1270	1132	1175	1232
Sulfur	ppm	ASTM D5185(m)	2060	2694	2444	2339
Oxidation	Abs/.1mm	ASTM D7414*	>25	13.4	18.5	17.5
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	14.4	13.9	13.9



ISO 17025:2017
Accredited
Laboratory

Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0107148
Lab Number : 02608662
Unique Number : 5709748
Test Package : MOB 1 (Additional Tests: Visual)

GFL Environmental - 217 - Aurora
 14131 BAYVIEW AVE, AURORA YARD
 AURORA, ON
 CA L4G 0K6
 Contact: Mike Havens
 MHavens@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
 F: (905)713-2445