



OIL ANALYSIS REPORT

| | |
|-----------------|--------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
1367
 Component
Rear Diesel Engine
 Fluid
PETRO CANADA DURON HP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | WC0887378 | WC0864972 | WC0864998 |
| Sample Date | | Client Info | | 03 Jan 2024 | 26 Oct 2023 | 11 Oct 2023 |
| Machine Age | hrs | Client Info | | 33970 | 33375 | 32869 |
| Oil Age | hrs | Client Info | | 595 | 506 | 463 |
| Filter Age | hrs | Client Info | | 0 | 0 | 463 |
| Oil Changed | | Client Info | | Changed | Changed | Changed |
| Filter Changed | | Client Info | | Changed | Changed | Changed |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|----------|-----|---------------|------|--------------|----|----|
| Iron | ppm | ASTM D5185(m) | >100 | 15 | 5 | 18 |
| Chromium | ppm | ASTM D5185(m) | >20 | <1 | 0 | <1 |
| Nickel | ppm | ASTM D5185(m) | >4 | <1 | 0 | 0 |
| Titanium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185(m) | >3 | 0 | <1 | <1 |
| Aluminum | ppm | ASTM D5185(m) | >20 | 2 | <1 | 1 |
| Lead | ppm | ASTM D5185(m) | >40 | <1 | 0 | <1 |
| Copper | ppm | ASTM D5185(m) | >330 | 1 | <1 | 2 |
| Tin | ppm | ASTM D5185(m) | >15 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |

CONTAMINATION










There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|---------------|------|----------------|------|------|
| Silicon | ppm | ASTM D5185(m) | >25 | 3 | 2 | 4 |
| Potassium | ppm | ASTM D5185(m) | >20 | 0 | 0 | 0 |
| Fuel | | WC Method | >5 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | ASTM D7844* | >3 | 1.9 | 0.5 | 1.7 |
| Nitration | Abs/cm | ASTM D7624* | >20 | 9.8 | 5.8 | 9.4 |
| Sulfation | Abs/.1mm | ASTM D7415* | >30 | 25.5 | 20.0 | 26.2 |
| Emulsified Water | scalar | Visual* | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|--------------|----------|---------------|------|-------------|------|------|
| Sodium | ppm | ASTM D5185(m) | | 1 | 2 | 2 |
| Boron | ppm | ASTM D5185(m) | 0 | 1 | 1 | 1 |
| Barium | ppm | ASTM D5185(m) | 0 | 0 | <1 | <1 |
| Molybdenum | ppm | ASTM D5185(m) | 60 | 57 | 58 | 59 |
| Manganese | ppm | ASTM D5185(m) | 0 | 0 | 0 | 0 |
| Magnesium | ppm | ASTM D5185(m) | 1010 | 942 | 927 | 941 |
| Calcium | ppm | ASTM D5185(m) | 1070 | 1044 | 1014 | 1030 |
| Phosphorus | ppm | ASTM D5185(m) | 1150 | 983 | 976 | 987 |
| Zinc | ppm | ASTM D5185(m) | 1270 | 1155 | 1161 | 1167 |
| Sulfur | ppm | ASTM D5185(m) | 2060 | 2609 | 2541 | 2454 |
| Oxidation | Abs/.1mm | ASTM D7414* | >25 | 21.6 | 15.7 | 23.2 |
| Visc @ 100°C | cSt | ASTM D7279(m) | 15.6 | 13.6 | 14.1 | 13.6 |



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0887378 **Received** : 16 Jan 2024
Lab Number : 02608886 **Diagnosed** : 16 Jan 2024
Unique Number : 5709972 **Diagnostician** : Wes Davis
Test Package : MOB 1

KINGSTON TRANSIT
 1181 JOHN COUNTER BLVD
 KINGSTON, ON
 CA K7K 6C7
 Contact: Brent Gunter
 bgunter@cityofkingston.ca
 T: (613)546-4291
 F: (613)542-1504

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.