

Machine Id
WESTERN 19-20
Component
Diesel Engine
Fluid
PETRO CANADA DURON UHP 5W40 (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PC0068992	PC0063385	PC0063380
Sample Date		Client Info		11 Jan 2024	13 Jun 2023	30 May 2023
Machine Age	hrs	Client Info		7211	6804	6488
Oil Age	hrs	Client Info		395	600	380
Filter Age	hrs	Client Info		395	600	380
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>100	8	20	7
Chromium	ppm	ASTM D5185(m)	>20	<1	3	<1
Nickel	ppm	ASTM D5185(m)	>4	0	<1	<1
Titanium	ppm	ASTM D5185(m)		0	<1	<1
Silver	ppm	ASTM D5185(m)	>3	0	0	0
Aluminum	ppm	ASTM D5185(m)	>20	5	▲ 23	3
Lead	ppm	ASTM D5185(m)	>40	0	0	<1
Copper	ppm	ASTM D5185(m)	>330	3	5	4
Tin	ppm	ASTM D5185(m)	>15	<1	<1	0
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION


La teneur en eau est négligeable. Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>25	3	7	3
Potassium	ppm	ASTM D5185(m)	>20	6	4	3
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water	%	ASTM D6304*	>0.2	0.022	---	---
ppm Water	ppm	ASTM D6304*	>2000	222	---	---
Glycol	%	ASTM D7922*		0.0	NEG	NEG
Soot %	%	ASTM D7844*	>3	0.1	0.1	0.1
Nitration	Abs/cm	ASTM D7624*	>20	8.3	8.6	8.3
Sulfation	Abs/.1mm	ASTM D7415*	>30	20.7	21.1	20.5
Emulsified Water	scalar	Visual*	>0.2	.2%	NEG	NEG

FLUID CONDITION

Le résultat pour le BN indique que la réserve d'alcalinité est acceptable pour l'huile. L'état de l'huile permet d'en prolonger l'utilisation.

Sodium	ppm	ASTM D5185(m)		4	15	6
Boron	ppm	ASTM D5185(m)	65	33	32	36
Barium	ppm	ASTM D5185(m)	0	0	0	0
Molybdenum	ppm	ASTM D5185(m)	65	54	59	59
Manganese	ppm	ASTM D5185(m)	0	0	<1	<1
Magnesium	ppm	ASTM D5185(m)	1160	1032	1027	1023
Calcium	ppm	ASTM D5185(m)	820	837	928	859
Phosphorus	ppm	ASTM D5185(m)	1160	956	1035	1014
Zinc	ppm	ASTM D5185(m)	1260	1132	1175	1140
Sulfur	ppm	ASTM D5185(m)	3000	2736	2716	2688
Oxidation	Abs/.1mm	ASTM D7414*	>25	17.8	18.3	17.8
Base Number (BN)	mg KOH/g	ASTM D2896*	11.0	9.84	8.88	8.99
Visc @ 40°C	cSt	ASTM D7279(m)	95.1	84.0	85.2	84.8
Visc @ 100°C	cSt	ASTM D7279(m)	14.3	13.6	13.6	13.7
Viscosity Index (VI)	Scale	ASTM D2270*	169	165	162	165



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0068992 **Received** : 17 Jan 2024
Lab Number : 02609214 **Diagnosed** : 18 Jan 2024
Unique Number : 5710300 **Diagnostician** : Wes Davis
Test Package : MOB 2 (Additional Tests: Glycol, KF, KV40, VI)

BETONNIERE LA TUQUE
 2990 PLACE INDUSTRIELLE
 LA TUQUE, QC
 CA G9X 4T1
 Contact: Shop Manager
 sylvain.blais@betonlit.com
 T: (819)523-7179
 F: (819)523-6931

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.