



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR L556 053565-1332

Component
Hydraulic System

Fluid
PETRO CANADA HYDREX XV ALL SEASON HYDRAULIC OIL (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH	LH	LH
Sample Date		Client Info		12 Jan 2024	08 Dec 2023	15 Sep 2023
Machine Age	hrs	Client Info		16000	15500	15032
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>20	6	6	9
Chromium	ppm	ASTM D5185(m)	>10	5	4	7
Nickel	ppm	ASTM D5185(m)	>10	0	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	<1	0
Aluminum	ppm	ASTM D5185(m)	>10	<1	<1	<1
Lead	ppm	ASTM D5185(m)	>10	<1	<1	1
Copper	ppm	ASTM D5185(m)	>75	1	1	2
Tin	ppm	ASTM D5185(m)	>10	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION









La propreté du système est acceptable pour votre objectif de propreté ISO 4406. La propreté du système et du fluide est acceptable.

Silicon	ppm	ASTM D5185(m)	>20	<1	<1	1
Potassium	ppm	ASTM D5185(m)	>20	0	0	1
Water		WC Method	>0.1	NEG	NEG	NEG
Particles >4µm		ASTM D7647	>20000	9103	5192	2205
Particles >6µm		ASTM D7647	>5000	2073	1050	585
Particles >14µm		ASTM D7647	>640	121	70	49
Particles >21µm		ASTM D7647	>160	32	17	10
Particles >38µm		ASTM D7647	>40	4	3	0
Particles >71µm		ASTM D7647	>10	1	1	0
Oil Cleanliness		ISO 4406 (c)	>21/19/16	20/18/14	20/17/13	18/16/13
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

L'état de l'huile est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		<1	<1	<1
Boron	ppm	ASTM D5185(m)	0	0	<1	<1
Barium	ppm	ASTM D5185(m)	0	0	<1	0
Molybdenum	ppm	ASTM D5185(m)	0	0	0	0
Manganese	ppm	ASTM D5185(m)	1	0	0	0
Magnesium	ppm	ASTM D5185(m)	0	1	<1	1
Calcium	ppm	ASTM D5185(m)	100	116	125	130
Phosphorus	ppm	ASTM D5185(m)	670	664	644	678
Zinc	ppm	ASTM D5185(m)	850	828	840	840
Sulfur	ppm	ASTM D5185(m)	1600	1658	1568	1630
Visc @ 40°C	cSt	ASTM D7279(m)	47.9	44.1	44.0	42.4



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH **Received** : 17 Jan 2024
Lab Number : 02609434 **Diagnosed** : 19 Jan 2024
Unique Number : 5710520 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: PrtCount)

NEXOLIA, CHAPPAIS ENERGIE SEC
 140 RUE DE LA CONGENERATION
 CHAPPAIS, QC
 CA G0W 1H0
 Contact: Carl Adams

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T: (418)745-2521
 F: (418)745-3680