



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(358696)
Machine Id
LIEBHERR R924LC 050422-1487
Component
Left Final Drive
Fluid
LIEBHERR GEAR BASIC 90 LS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0278864	LH0274649	LH0247160
Sample Date		Client Info		10 Jan 2024	14 Aug 2023	06 Jan 2023
Machine Age	hrs	Client Info		4848	4043	2975
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	SEVERE

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>1525	383	676	3563
Chromium	ppm	ASTM D5185(m)	>25	5	6	35
Nickel	ppm	ASTM D5185(m)	>5	2	2	7
Titanium	ppm	ASTM D5185(m)	>8	<1	1	12
Silver	ppm	ASTM D5185(m)		0	<1	0
Aluminum	ppm	ASTM D5185(m)	>90	18	24	191
Lead	ppm	ASTM D5185(m)	>8	0	0	<1
Copper	ppm	ASTM D5185(m)	>85	<1	<1	2
Tin	ppm	ASTM D5185(m)	>5	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	<1
White Metal	scalar	Visual*	NONE	NONE	LIGHT	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>460	83	110	874
Potassium	ppm	ASTM D5185(m)	>20	8	10	68
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	VLITE	LIGHT	VLITE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		14	10	63
Boron	ppm	ASTM D5185(m)	0	39	14	87
Barium	ppm	ASTM D5185(m)	0	0	<1	0
Molybdenum	ppm	ASTM D5185(m)	0	0	<1	2
Manganese	ppm	ASTM D5185(m)	0	3	6	25
Magnesium	ppm	ASTM D5185(m)	<1	6	11	54
Calcium	ppm	ASTM D5185(m)	<1	29	40	217
Phosphorus	ppm	ASTM D5185(m)	2143	2052	2267	1811
Zinc	ppm	ASTM D5185(m)	<1	15	22	26
Sulfur	ppm	ASTM D5185(m)	23468	24164	25816	32949
Visc @ 40°C	cSt	ASTM D7279(m)	170	160	171	140



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0278864 **Received** : 23 Jan 2024
Lab Number : 02610667 **Diagnosed** : 23 Jan 2024
Unique Number : 5711753 **Diagnostician** : Wes Davis
Test Package : MOB 1

SL EXCAVATION INC.
 4626 COUNTY ROAD 29
 ALMONTE, ON
 CA K0A 1A0
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: