



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(360382)
Machine Id
LIEBHERR LH60C 119564-1528
Component
Swing Drive
Fluid
PETRO CANADA TRAXON 75W90 SYNTHETIC (14 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0278915	LH0234858	LH0242600
Sample Date		Client Info		18 Jan 2024	23 Jun 2023	28 Oct 2022
Machine Age	hrs	Client Info		4002	2997	1996
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>350	247	215	294
Chromium	ppm	ASTM D5185(m)	>15	2	2	2
Nickel	ppm	ASTM D5185(m)	>5	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	3	<1
Aluminum	ppm	ASTM D5185(m)	>5	<1	<1	<1
Lead	ppm	ASTM D5185(m)	>10	1	2	1
Copper	ppm	ASTM D5185(m)	>300	55	58	57
Tin	ppm	ASTM D5185(m)	>15	1	1	2
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	VLITE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>15	1	2	2
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	VLITE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		1	2	4
Boron	ppm	ASTM D5185(m)	328	268	242	138
Barium	ppm	ASTM D5185(m)	1	<1	2	3
Molybdenum	ppm	ASTM D5185(m)		0	0	0
Manganese	ppm	ASTM D5185(m)		1	2	2
Magnesium	ppm	ASTM D5185(m)	1	3	2	2
Calcium	ppm	ASTM D5185(m)	7	21	29	48
Phosphorus	ppm	ASTM D5185(m)	1145	1321	1505	1863
Zinc	ppm	ASTM D5185(m)	3	14	20	18
Sulfur	ppm	ASTM D5185(m)	17909	21010	21139	22679
Visc @ 40°C	cSt	ASTM D7279(m)	99.6	106	113	133



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0278915 **Received** : 23 Jan 2024
Lab Number : 02610694 **Diagnosed** : 23 Jan 2024
Unique Number : 5711780 **Diagnostician** : Wes Davis
Test Package : MOB 1

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

GERDAU AMERISTEEL
 3000 COPELAND DR
 CORNWALL, ON
 CA K6H 6P7
 Contact: Ross Cotton
 cotton@gerdauameristeel.com
 T: (613)933-1119
 F: (613)933-6142