



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
[83549]

Machine Id
40 CORONATION DRIVE SCARBOROUGH CITY OF TORONTO 3002627540

Component
Left Natural Gas Engine

Fluid
ESSO XD-3 EXTRA 15W40 (10 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PN0005628	PN0004413	PN0002022
Sample Date		Client Info		19 Jan 2024	09 Jan 2023	15 Jan 2021
Machine Age	hrs	Client Info		81	68	37
Oil Age	hrs	Client Info		15	14	17
Filter Age	hrs	Client Info		15	14	17
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185(m)	>50	5	5	8
Chromium	ppm	ASTM D5185(m)	>4	0	0	<1
Nickel	ppm	ASTM D5185(m)	>2	<1	0	<1
Titanium	ppm	ASTM D5185(m)		0	<1	0
Silver	ppm	ASTM D5185(m)	>3	0	0	<1
Aluminum	ppm	ASTM D5185(m)	>9	2	3	2
Lead	ppm	ASTM D5185(m)	>30	<1	0	<1
Copper	ppm	ASTM D5185(m)	>35	2	3	3
Tin	ppm	ASTM D5185(m)	>4	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	NONE	---	---

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>+100	9	16	21
Potassium	ppm	ASTM D5185(m)	>20	2	<1	2
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		---	---	0.0
Soot %	%	ASTM D7844*		0	0	0
Nitration	Abs/cm	ASTM D7624*	>20	7.0	7.3	6.0
Sulfation	Abs/.1mm	ASTM D7415*	>30	17.0	18.2	16.7
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	NORML	---
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	.2%

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>192	2	3	2
Boron	ppm	ASTM D5185(m)		62	72	91
Barium	ppm	ASTM D5185(m)		0	0	0
Molybdenum	ppm	ASTM D5185(m)		37	87	68
Manganese	ppm	ASTM D5185(m)		0	<1	<1
Magnesium	ppm	ASTM D5185(m)		195	93	600
Calcium	ppm	ASTM D5185(m)	3780	1909	2093	1158
Phosphorus	ppm	ASTM D5185(m)	1370	971	1037	625
Zinc	ppm	ASTM D5185(m)	1500	1074	1065	732
Sulfur	ppm	ASTM D5185(m)	3800	3244	3111	1801
Oxidation	Abs/.1mm	ASTM D7414*	>25	13.2	13.0	11.2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	13.6	13.4	10.1



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PN0005628 **Received** : 24 Jan 2024
Lab Number : 02610869 **Diagnosed** : 24 Jan 2024
Unique Number : 5719964 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: Visual)

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

POWER STATION INC.
 1050 JAYSON COURT
 MISSISSAUGA, ON
 CA L4W 2V5
 Contact: Brett Kinkley
 Bkinkley@pwrstn.com
 T:
 F: (905)665-8544