

Area  
**MICHAUDVILLE**  
Machine Id  
**5010**  
Component  
**Front Differential**  
Fluid  
**TDTO FLUID SAE 30 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

**WEAR**

All component wear rates are normal.











**CONTAMINATION**

There is no indication of any contamination in the oil.

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>PC0083747</b>	PC0067652	PC0046378
Sample Date		Client Info		<b>19 Feb 2024</b>	11 Jan 2023	09 May 2021
Machine Age	hrs	Client Info		<b>14524</b>	14015	13566
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	ABNORMAL	ABNORMAL
Iron	ppm	ASTM D5185(m)	>500	<b>212</b>	10	7
Chromium	ppm	ASTM D5185(m)	>10	<b>0</b>	0	0
Nickel	ppm	ASTM D5185(m)	>10	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185(m)		<b>0</b>	<1	0
Silver	ppm	ASTM D5185(m)		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>25	<b>3</b>	2	1
Lead	ppm	ASTM D5185(m)	>25	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185(m)	>100	<b>2</b>	2	<1
Tin	ppm	ASTM D5185(m)	>10	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
White Metal	scalar	Visual*	NONE	<b>NONE</b>	VLITE	NONE
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Silicon	ppm	ASTM D5185(m)	>75	<b>16</b>	6	6
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0	<1
Water		WC Method	>.2	<b>NEG</b>	NEG	NEG
Silt	scalar	Visual*	NONE	<b>VLITE</b>	NONE	NONE
Debris	scalar	Visual*	NONE	<b>NONE</b>	VLITE	NONE
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	VLITE	NONE
Appearance	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>.2	<b>NEG</b>	NEG	NEG
Sodium	ppm	ASTM D5185(m)		<b>1</b>	<1	1
Boron	ppm	ASTM D5185(m)	37	<b>84</b>	1	2
Barium	ppm	ASTM D5185(m)	7	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185(m)	5	<b>&lt;1</b>	<1	<1
Manganese	ppm	ASTM D5185(m)		<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185(m)	40	<b>33</b>	12	13
Calcium	ppm	ASTM D5185(m)	2650	<b>3478</b>	3122	2965
Phosphorus	ppm	ASTM D5185(m)	1050	<b>1338</b>	1112	1017
Zinc	ppm	ASTM D5185(m)	1075	<b>1341</b>	1213	1247
Sulfur	ppm	ASTM D5185(m)	5750	<b>7289</b>	5032	5010
Visc @ 40°C	cSt	ASTM D7279(m)	101	<b>56.8</b>	▲ 60.9	▲ 61.8
Visc @ 100°C	cSt	ASTM D7279(m)	10.9	<b>8.9</b>	10.6	10.6
Viscosity Index (VI)	Scale	ASTM D2270*	90	<b>134</b>	165	▲ 162



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : PC0083747  
**Lab Number** : 02616755  
**Unique Number** : 5733865  
**Test Package** : MOB 1 ( Additional Tests: KV100, VI )  
**Received** : 20 Feb 2024  
**Tested** : 20 Feb 2024  
**Diagnosed** : 20 Feb 2024 - Wes Davis

**LES ENTREPRISES MICHAUVILLE INC.**  
 270 RUE BRUNET  
 MONT ST-HILAIRE, QC  
 CA J3H 0M6  
 Contact: Martin Trudel  
 mtrudel@michaudville.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.

T:  
F: