

# [001315-1]

## COSTCO #1169 MISSISSAUGA RACK "A" HILL PHOENIX RACK MOPDEL #69454 (S/N 410000033074)

## **Reciprocating Compressor**

## EMKARATE RL 32H (--- GAL)

### RECOMMENDATION

Resample at the next service interval to monitor. Please note that there was insufficient sample submitted to perform all assigned tests.

| MAV. |  |
|------|--|
|      |  |
|      |  |

All component wear rates are normal.

\_\_\_\_\_

#### CONTAMINATION

Insufficient sample was received to conduct all the routine laboratory tests.

FLUID CONDITION

The condition of the oil is acceptable for the time in service (unconfirmed).

|                  |          |               |           |             | ,           |             |
|------------------|----------|---------------|-----------|-------------|-------------|-------------|
| Test             | UOM      | Method        | Limit/Abn | Current     | History1    | History2    |
| Sample Number    |          | Client Info   |           | WC0907693   | WC0672580   | WC0556252   |
| Sample Date      |          | Client Info   |           | 09 Feb 2024 | 22 Feb 2022 | 28 Feb 2021 |
| Machine Age      | yrs      | Client Info   |           | 10          | 7           | 10          |
| Oil Age          | yrs      | Client Info   |           | 10          | 7           | 10          |
| Filter Age       | yrs      | Client Info   |           | 1           | 1           | 1           |
| Oil Changed      |          | Client Info   |           | N/A         | N/A         | Changed     |
| Filter Changed   |          | Client Info   |           | N/A         | N/A         | Changed     |
| Sample Status    |          |               |           | NORMAL      | NORMAL      | NORMAL      |
|                  |          |               |           |             |             |             |
| Iron             | ppm      | ASTM D5185(m) | >50       | <1          | <1          | <1          |
| Chromium         | ppm      | ASTM D5185(m) | >10       | 0           | 0           | 0           |
| Nickel           | ppm      | ASTM D5185(m) |           | 0           | 0           | 0           |
| Titanium         | ppm      | ASTM D5185(m) |           | 0           | 0           | 0           |
| Silver           | ppm      | ASTM D5185(m) |           | 0           | 0           | 0           |
| Aluminum         | ppm      | ASTM D5185(m) | >25       | <1          | <1          | <1          |
| Lead             | ppm      | ASTM D5185(m) | >25       | <1          | <1          | 0           |
| Copper           | ppm      | ASTM D5185(m) | >50       | 4           | 3           | 2           |
| Tin              | ppm      | ASTM D5185(m) | >15       | 0           | <1          | 0           |
| Vanadium         | ppm      | ASTM D5185(m) |           | 0           | 0           | 0           |
| White Metal      | scalar   | Visual*       | NONE      | NONE        | NONE        | NONE        |
| Yellow Metal     | scalar   | Visual*       | NONE      | NONE        | NONE        | NONE        |
| Silicon          | ppm      | ASTM D5185(m) | >25       | 1           | 2           | 2           |
| Potassium        | ppm      | ASTM D5185(m) | >20       | <1          | <1          | <1          |
| Water            | %        | ASTM D6304*   | >0.1      | 0.047       |             |             |
| ppm Water        | ppm      | ASTM D6304*   | >1000     | 478         |             |             |
| Silt             | scalar   | Visual*       | NONE      | NONE        | NONE        | NONE        |
| Debris           | scalar   | Visual*       | NONE      | NONE        | VLITE       | NONE        |
| Sand/Dirt        | scalar   | Visual*       | NONE      | NONE        | NONE        | NONE        |
| Appearance       | scalar   | Visual*       | NORML     | NORML       | NORML       | NORML       |
| Odor             | scalar   | Visual*       | NORML     | NORML       | FREON       | NORML       |
| Sodium           | ppm      | ASTM D5185(m) |           | 0           | 0           | 0           |
| Boron            | ppm      | ASTM D5185(m) | 0         | <1          | <1          | <1          |
| Barium           | ppm      | ASTM D5185(m) | 0         | 0           | 0           | 0           |
| Molybdenum       | ppm      | ASTM D5185(m) | 0         | 0           | 0           | 0           |
| Manganese        | ppm      | ASTM D5185(m) |           | 0           | 0           | 0           |
| Magnesium        | ppm      | ASTM D5185(m) | 0         | 0           | 0           | <1          |
| Calcium          | ppm      | ASTM D5185(m) | 0         | 0           | 0           | 0           |
| Phosphorus       | ppm      | ASTM D5185(m) | 5         | 0           | <1          | <1          |
| Zinc             | ppm      | ASTM D5185(m) | 10        | <1          | <1          | <1          |
| Sulfur           | ppm      | ASTM D5185(m) | 50        | 0           | <1          | 8           |
| Acid Number (AN) | mg KOH/g | ASTM D974*    | .05       | 0.04        | 0.01        | 0.04        |
| Visc @ 40°C      | cSt      | ASTM D7279(m) | 31.5      |             | 29.6        | 28.4        |
|                  |          |               | 00        |             | _0.0        | _0.1        |

Contact/Location: Mike Squires - NEEBUR



