



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(374940)
Machine Id
LIEBHERR LH30M 137944-1253
Component
Rear Differential
Fluid
{not provided} (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0278724	LH0239296	---
Sample Date		Client Info		22 Feb 2024	31 Aug 2022	---
Machine Age	hrs	Client Info		2777	551	---
Oil Age	hrs	Client Info		0	0	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		N/A	N/A	---
Sample Status				NORMAL	NORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>190	6	7	---
Chromium	ppm	ASTM D5185(m)	>2	0	<1	---
Nickel	ppm	ASTM D5185(m)	>2	<1	0	---
Titanium	ppm	ASTM D5185(m)		0	<1	---
Silver	ppm	ASTM D5185(m)		0	0	---
Aluminum	ppm	ASTM D5185(m)	>5	<1	<1	---
Lead	ppm	ASTM D5185(m)	>15	<1	<1	---
Copper	ppm	ASTM D5185(m)	>70	7	4	---
Tin	ppm	ASTM D5185(m)	>2	0	0	---
Vanadium	ppm	ASTM D5185(m)		0	0	---
White Metal	scalar	Visual*	NONE	NONE	NONE	---
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	---

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	2	8	---
Potassium	ppm	ASTM D5185(m)	>20	<1	6	---
Water		WC Method	>.2	NEG	NEG	---
Silt	scalar	Visual*	NONE	NONE	NONE	---
Debris	scalar	Visual*	NONE	NONE	NONE	---
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	---
Appearance	scalar	Visual*	NORML	NORML	NORML	---
Odor	scalar	Visual*	NORML	NORML	NORML	---
Emulsified Water	scalar	Visual*	>.2	NEG	NEG	---

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		3	14	---
Boron	ppm	ASTM D5185(m)		256	99	---
Barium	ppm	ASTM D5185(m)		0	<1	---
Molybdenum	ppm	ASTM D5185(m)		0	0	---
Manganese	ppm	ASTM D5185(m)		0	3	---
Magnesium	ppm	ASTM D5185(m)		4	11	---
Calcium	ppm	ASTM D5185(m)		416	3551	---
Phosphorus	ppm	ASTM D5185(m)		1254	1186	---
Zinc	ppm	ASTM D5185(m)		177	1366	---
Sulfur	ppm	ASTM D5185(m)		18204	2924	---
Visc @ 40°C	cSt	ASTM D7279(m)		94.8	64.8	---



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0278724 **Received** : 23 Feb 2024
Lab Number : 02617726 **Tested** : 23 Feb 2024
Unique Number : 5734836 **Diagnosed** : 23 Feb 2024 - Wes Davis
Test Package : MOB 1

KINGS AUTO WRECKERS
 1866 DRUMMOND LINE
 PETERBOROUGH, ON
 CA K9J 6X8
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: