



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
810042

Component
2 Differential

Fluid
GEAR OIL SAE 75W90 (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0110458	GFL0068237	---
Sample Date		Client Info		07 Feb 2024	08 Feb 2023	---
Machine Age	hrs	Client Info		2520	1440	---
Oil Age	hrs	Client Info		2520	1440	---
Filter Age	hrs	Client Info		2520	1440	---
Oil Changed		Client Info		N/A	N/A	---
Filter Changed		Client Info		N/A	N/A	---
Sample Status				NORMAL	NORMAL	---

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>500	126	92	---
Chromium	ppm	ASTM D5185(m)	>10	1	1	---
Nickel	ppm	ASTM D5185(m)	>10	<1	<1	---
Titanium	ppm	ASTM D5185(m)		0	<1	---
Silver	ppm	ASTM D5185(m)		0	0	---
Aluminum	ppm	ASTM D5185(m)	>25	3	2	---
Lead	ppm	ASTM D5185(m)	>25	<1	0	---
Copper	ppm	ASTM D5185(m)	>100	2	2	---
Tin	ppm	ASTM D5185(m)	>10	0	<1	---
Vanadium	ppm	ASTM D5185(m)		0	0	---
White Metal	scalar	Visual*	NONE	NONE	NONE	---
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	---

CONTAMINATION










Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>75	28	29	---
Potassium	ppm	ASTM D5185(m)	>20	2	<1	---
Water		WC Method	>.2	NEG	NEG	---
Silt	scalar	Visual*	NONE	NONE	NONE	---
Debris	scalar	Visual*	NONE	NONE	NONE	---
Sand/Dirt	scalar	Visual*	NONE	NONE	VLITE	---
Appearance	scalar	Visual*	NORML	NORML	NORML	---
Odor	scalar	Visual*	NORML	NORML	NORML	---
Emulsified Water	scalar	Visual*	>.2	NEG	NEG	---

FLUID CONDITION

L'état de l'huile est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		9	11	---
Boron	ppm	ASTM D5185(m)	400	212	233	---
Barium	ppm	ASTM D5185(m)	200	5	2	---
Molybdenum	ppm	ASTM D5185(m)	12	0	0	---
Manganese	ppm	ASTM D5185(m)		11	12	---
Magnesium	ppm	ASTM D5185(m)	12	2	2	---
Calcium	ppm	ASTM D5185(m)	150	9	7	---
Phosphorus	ppm	ASTM D5185(m)	1650	1374	1520	---
Zinc	ppm	ASTM D5185(m)	125	16	18	---
Sulfur	ppm	ASTM D5185(m)	22500	23077	24892	---
Visc @ 40°C	cSt	ASTM D7279(m)	109	98.7	99.6	---



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0110458
Lab Number : 02618998
Unique Number : 5736108
Test Package : MOB 1
Received : 29 Feb 2024
Tested : 29 Feb 2024
Diagnosed : 29 Feb 2024 - Wes Davis

GFL Environmental - 732 - Beauce - Hauling - Solid Waste
 139, 181 Street,
 Beauceville, QC
 CA G5X 2S9
 Contact: Sandrine Duval
 sduval@matrec.ca
 T: (418)774-5275
 F: (418)774-5292

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.