



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(354957)
Machine Id
LIEBHERR R918LC 053128-1721
Component
Left Final Drive
Fluid
LIEBHERR GEAR BASIC 90 LS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH	LH0260815	LH0239158
Sample Date		Client Info		19 Feb 2024	15 May 2023	19 Aug 2022
Machine Age	hrs	Client Info		3908	2992	1980
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>500	163	▲ 721	368
Chromium	ppm	ASTM D5185(m)	>10	2	8	5
Nickel	ppm	ASTM D5185(m)	>10	1	2	2
Titanium	ppm	ASTM D5185(m)		0	9	2
Silver	ppm	ASTM D5185(m)		0	0	0
Aluminum	ppm	ASTM D5185(m)	>25	12	● 134	34
Lead	ppm	ASTM D5185(m)	>25	<1	<1	0
Copper	ppm	ASTM D5185(m)	>50	<1	<1	<1
Tin	ppm	ASTM D5185(m)	>10	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	<1	<1
White Metal	scalar	Visual*	NONE	LIGHT	NONE	VLITE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>75	46	▲ 528	129
Potassium	ppm	ASTM D5185(m)	>20	4	37	11
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	MODER	LIGHT	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		5	42	14
Boron	ppm	ASTM D5185(m)	0	2	1	1
Barium	ppm	ASTM D5185(m)	0	0	<1	<1
Molybdenum	ppm	ASTM D5185(m)	0	0	<1	<1
Manganese	ppm	ASTM D5185(m)	0	2	7	4
Magnesium	ppm	ASTM D5185(m)	<1	4	22	7
Calcium	ppm	ASTM D5185(m)	<1	18	66	27
Phosphorus	ppm	ASTM D5185(m)	2143	2163	2455	2225
Zinc	ppm	ASTM D5185(m)	<1	12	12	24
Sulfur	ppm	ASTM D5185(m)	23468	25664	26595	34925
Visc @ 40°C	cSt	ASTM D7279(m)	170	179	178	179



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH
Lab Number : 02619022
Unique Number : 5736132
Test Package : MOB 1
Received : 29 Feb 2024
Tested : 29 Feb 2024
Diagnosed : 29 Feb 2024 - Wes Davis

Polyexcave Inc.
 787 Ch. Du Moine
 St-Anne de Sorel, QC
 CA J3P 5N3
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: