



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
(CFAQR)
Machine Id
[CFAQR] PA31-350 L-5368-61A
Component
Left Piston Aircraft Engine
Fluid
PHILLIPS 66 AVIATION X/C OIL SAE20W50 (14 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0886706	WC0838449	WC0754570
Sample Date		Client Info		23 Feb 2024	12 Feb 2024	27 Oct 2023
TSN	hrs	Client Info		0	0	0
TSO	hrs	Client Info		3468	3445	3255
Oil Age	hrs	Client Info		23	51	52
Filter Age	hrs	Client Info		23	51	52
Oil Changed		Client Info		Not Changed	Changed	Changed
Filter Changed		Client Info		Not Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>80	35	56	48
Chromium	ppm	ASTM D5185(m)	>40	10	15	10
Nickel	ppm	ASTM D5185(m)	>15	13	▲ 20	14
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>5	<1	<1	<1
Aluminum	ppm	ASTM D5185(m)	>25	5	8	4
Lead	ppm	ASTM D5185(m)	>20000	5409	8460	6054
Copper	ppm	ASTM D5185(m)	>25	5	8	5
Tin	ppm	ASTM D5185(m)	>30	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>15	6	7	6
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	0
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Silt	scalar	Visual*	NONE	VLITE	VLITE	NONE
Debris	scalar	Visual*	NONE	VLITE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	WGOIL
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	.2%

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<1	0	<1
Boron	ppm	ASTM D5185(m)	0.0	0	0	0
Barium	ppm	ASTM D5185(m)	0.0	0	0	0
Molybdenum	ppm	ASTM D5185(m)	0.0	0	0	0
Manganese	ppm	ASTM D5185(m)	0.0	0	0	0
Magnesium	ppm	ASTM D5185(m)	0.0	3	6	3
Calcium	ppm	ASTM D5185(m)	4.7	<1	1	4
Phosphorus	ppm	ASTM D5185(m)	0.0	0	0	1
Zinc	ppm	ASTM D5185(m)	0.1	2	2	4
Sulfur	ppm	ASTM D5185(m)	848	1024	1085	865
Visc @ 100°C	cSt	ASTM D7279(m)	20.2	20.7	21.7	21.2



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0886706
Lab Number : 02619260
Unique Number : 5736370
Test Package : AVI 1
Received : 01 Mar 2024
Tested : 01 Mar 2024
Diagnosed : 01 Mar 2024 - Kevin Marson

SKYCAR AIR AMBULANCE
 BOX 289, 17 AIRPORT ROAD
 SIOUX LOOKOUT, ON
 CA P8T 1A3
 Contact: Jason Murphy
 prm@skycare.ca
 T: (807)737-0039
 F: (807)737-0040

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.