



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**811016**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (20 LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0059104</b>	GFL0059069	GFL0059066
Sample Date		Client Info		<b>30 Jan 2024</b>	31 Oct 2023	04 Aug 2023
Machine Age	hrs	Client Info		<b>0</b>	0	0
Oil Age	hrs	Client Info		<b>600</b>	600	600
Filter Age	hrs	Client Info		<b>600</b>	600	600
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>80	<b>20</b>	13	13
Chromium	ppm	ASTM D5185(m)	>5	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>3	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185(m)	>30	<b>3</b>	2	2
Lead	ppm	ASTM D5185(m)	>30	<b>&lt;1</b>	<1	0
Copper	ppm	ASTM D5185(m)	>150	<b>2</b>	1	1
Tin	ppm	ASTM D5185(m)	>5	<b>&lt;1</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0

**CONTAMINATION**










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	<b>4</b>	4	5
Potassium	ppm	ASTM D5185(m)	>20	<b>4</b>	1	2
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	ASTM D7844*	>3	<b>0.3</b>	0.2	0.2
Nitration	Abs/cm	ASTM D7624*	>20	<b>9.9</b>	8.6	9.4
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>20.5</b>	19.6	20.1
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<b>2</b>	2	2
Boron	ppm	ASTM D5185(m)	0	<b>4</b>	4	6
Barium	ppm	ASTM D5185(m)	0	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185(m)	60	<b>58</b>	58	59
Manganese	ppm	ASTM D5185(m)	0	<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185(m)	1010	<b>947</b>	945	967
Calcium	ppm	ASTM D5185(m)	1070	<b>1046</b>	1011	1028
Phosphorus	ppm	ASTM D5185(m)	1150	<b>980</b>	960	1034
Zinc	ppm	ASTM D5185(m)	1270	<b>1166</b>	1179	1180
Sulfur	ppm	ASTM D5185(m)	2060	<b>2565</b>	2477	2521
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>18.2</b>	16.2	16.8
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	<b>13.8</b>	13.5	13.5



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0059104  
**Lab Number** : 02619498  
**Unique Number** : 5736608  
**Test Package** : MOB 1  
**Received** : 04 Mar 2024  
**Tested** : 04 Mar 2024  
**Diagnosed** : 04 Mar 2024 - Wes Davis

**GFL Environmental - 570 - Thunder Bay**  
 3000 Highway 61,  
 Slate River, ON  
 CA P7J 0G8  
 Contact: Cindy Wall  
 cwall@gflenv.com  
 T: (807)577-0411  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.