



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(341437)
Machine Id
LIEBHERR LH50M 128335-1216
Component
Splitter Box
Fluid
GEAR OIL SAE 75W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0274727	LH0277479	LH0270147
Sample Date		Client Info		03 Mar 2024	20 Nov 2023	27 Sep 2023
Machine Age	hrs	Client Info		12359	11104	10573
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>80	17	14	22
Chromium	ppm	ASTM D5185(m)	>2	<1	0	0
Nickel	ppm	ASTM D5185(m)	>2	<1	0	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	<1	0
Aluminum	ppm	ASTM D5185(m)	>5	<1	<1	<1
Lead	ppm	ASTM D5185(m)	>2	0	0	<1
Copper	ppm	ASTM D5185(m)	>10	<1	<1	1
Tin	ppm	ASTM D5185(m)	>2	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>10	<1	2	5
Potassium	ppm	ASTM D5185(m)	>20	<1	0	0
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	VLITE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	VLITE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>25	<1	<1	1
Boron	ppm	ASTM D5185(m)	400	260	224	77
Barium	ppm	ASTM D5185(m)	200	0	<1	<1
Molybdenum	ppm	ASTM D5185(m)	12	0	0	0
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)	12	2	1	1
Calcium	ppm	ASTM D5185(m)	150	45	29	37
Phosphorus	ppm	ASTM D5185(m)	1650	1195	1077	849
Zinc	ppm	ASTM D5185(m)	125	116	69	90
Sulfur	ppm	ASTM D5185(m)	22500	18610	19450	18552
Visc @ 40°C	cSt	ASTM D7279(m)	109	83.5	85.8	79.8



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0274727
Lab Number : 02619678
Unique Number : 5736788
Test Package : MOB 1
Received : 04 Mar 2024
Tested : 04 Mar 2024
Diagnosed : 04 Mar 2024 - Kevin Marson

COMBINED METAL INDUSTRIES-PUBLIC YARD
 129 FENMAR DR
 TORONTO, ON
 CA M9L 1M7
 Contact: Greg Sacher
 gsacher@combinedmetal.com
 T: (416)642-7262
 F: x:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.