



# LIEBHERR

## OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**(341437)**  
Machine Id  
**LIEBHERR LH50M 128335-1216**  
Component  
**Rear Differential**  
Fluid  
**GEAR OIL SAE 75W90 (24 LTR)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LH0274730</b>	LH0277472	LH0270154
Sample Date		Client Info		<b>03 Mar 2024</b>	20 Nov 2023	27 Sep 2023
Machine Age	hrs	Client Info		<b>12359</b>	11104	10573
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Changed	N/A
Filter Changed		Client Info		<b>None</b>	None	None
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>190	<b>13</b>	36	6
Chromium	ppm	ASTM D5185(m)	>2	<b>0</b>	0	0
Nickel	ppm	ASTM D5185(m)	>2	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)		<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185(m)	>5	<b>&lt;1</b>	0	0
Lead	ppm	ASTM D5185(m)	>15	<b>0</b>	<1	0
Copper	ppm	ASTM D5185(m)	>70	<b>4</b>	15	4
Tin	ppm	ASTM D5185(m)	>2	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
White Metal	scalar	Visual*	NONE	<b>VLITE</b>	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	<b>1</b>	1	2
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0	0
Water		WC Method	>.2	<b>NEG</b>	NEG	NEG
Silt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<b>&lt;1</b>	2	1
Boron	ppm	ASTM D5185(m)	400	<b>293</b>	269	274
Barium	ppm	ASTM D5185(m)	200	<b>0</b>	<1	<1
Molybdenum	ppm	ASTM D5185(m)	12	<b>0</b>	0	0
Manganese	ppm	ASTM D5185(m)		<b>0</b>	0	0
Magnesium	ppm	ASTM D5185(m)	12	<b>1</b>	1	<1
Calcium	ppm	ASTM D5185(m)	150	<b>10</b>	8	10
Phosphorus	ppm	ASTM D5185(m)	1650	<b>1256</b>	1131	1188
Zinc	ppm	ASTM D5185(m)	125	<b>12</b>	8	10
Sulfur	ppm	ASTM D5185(m)	22500	<b>21196</b>	20766	20775
Visc @ 40°C	cSt	ASTM D7279(m)	109	<b>102</b>	102	104



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : LH0274730  
**Lab Number** : 02619680  
**Unique Number** : 5736790  
**Test Package** : MOB 1  
**Received** : 04 Mar 2024  
**Tested** : 04 Mar 2024  
**Diagnosed** : 04 Mar 2024 - Kevin Marson

**COMBINED METAL INDUSTRIES-PUBLIC YARD**  
 129 FENMAR DR  
 TORONTO, ON  
 CA M9L 1M7  
 Contact: Greg Sacher  
 gsacher@combinedmetal.com  
 T: (416)642-7262  
 F: x:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.