



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[395275]

Machine Id
16-8004

Component
Diesel Engine

Fluid
VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP392869	VCP391843	VCP394811
Sample Date		Client Info		24 Feb 2024	02 Nov 2023	26 Aug 2023
Machine Age	hrs	Client Info		24000	23500	23000
Oil Age	hrs	Client Info		500	500	500
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Not Changd	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>100	6	6	6
Chromium	ppm	ASTM D5185(m)	>10	0	0	<1
Nickel	ppm	ASTM D5185(m)	>10	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>2	0	<1	0
Aluminum	ppm	ASTM D5185(m)	>10	3	2	3
Lead	ppm	ASTM D5185(m)	>20	<1	<1	2
Copper	ppm	ASTM D5185(m)	>15	1	<1	<1
Tin	ppm	ASTM D5185(m)	>10	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	7	6	6
Potassium	ppm	ASTM D5185(m)	>20	3	0	0
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>3	0.4	0.7	0.9
Nitration	Abs/cm	ASTM D7624*	>20	7.3	7.7	7.7
Sulfation	Abs/.1mm	ASTM D7415*	>30	21.7	23.7	24.8
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		3	3	3
Boron	ppm	ASTM D5185(m)	2.5	35	25	27
Barium	ppm	ASTM D5185(m)	0.0	0	0	0
Molybdenum	ppm	ASTM D5185(m)	0.7	40	39	39
Manganese	ppm	ASTM D5185(m)	0.0	0	0	<1
Magnesium	ppm	ASTM D5185(m)	256	493	481	481
Calcium	ppm	ASTM D5185(m)	2057	1690	1659	1648
Phosphorus	ppm	ASTM D5185(m)	935	912	876	934
Zinc	ppm	ASTM D5185(m)	1223	1045	1032	1043
Sulfur	ppm	ASTM D5185(m)	4079	2487	2265	2297
Oxidation	Abs/.1mm	ASTM D7414*	>25	18.3	19.8	19.4
Visc @ 100°C	cSt	ASTM D7279(m)	15.0	12.1	12.3	12.8



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : VCP392869
Lab Number : 02620156
Unique Number : 5737266
Test Package : MOB 1
Received : 06 Mar 2024
Tested : 06 Mar 2024
Diagnosed : 06 Mar 2024 - Wes Davis

CRH CANADA GROUP INC.
 P.O. BOX 5400
 CONCORD, ON
 CA L4K 1B6
 Contact: Dan Brown
 dan.brown@ca.crh.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: