

WEAR CONTAMINATION FLUID CONDITION

NORMAL NORMAL NORMAL

[MC-001363]

TYLER RACK B (S/N W0387590T2)

Component Reciprocating Compressor

| {not provided} (10 LTR) | | | | | | | |
|---|------------------|----------|---------------|---------------|-------------|----------|----------|
| RECOMMENDATION | Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
| Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample. | Sample Number | | Client Info | | WC0907704 | | |
| | Sample Date | | Client Info | | 28 Feb 2024 | | |
| | Machine Age | hrs | Client Info | | 0 | | |
| | Oil Age | hrs | Client Info | | 0 | | |
| | Filter Age | hrs | Client Info | | 0 | | |
| | Oil Changed | | Client Info | | N/A | | |
| | Filter Changed | | Client Info | | N/A | | |
| | Sample Status | | | | NORMAL | | |
| WEAR | PQ | | ASTM D8184* | | 0 | | |
| All component wear rates are normal. | Iron | ppm | ASTM D5185(m) | >50 | <1 | | |
| | Chromium | ppm | ASTM D5185(m) | | 0 | | |
| | Nickel | ppm | ASTM D5185(m) | 710 | 0 | | |
| | Titanium | ppm | ASTM D5185(m) | | 0 | | |
| | Silver | ppm | ASTM D5185(m) | | 0 | | |
| | Aluminum | ppm | ASTM D5185(m) | >25 | <1 | | |
| | Lead | ppm | ASTM D5185(m) | >25 | <1 | | |
| | Copper | ppm | ASTM D5185(m) | >50 | <1 | | |
| | Tin | ppm | ASTM D5185(m) | >15 | 0 | | |
| | Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| | White Metal | scalar | Visual* | NONE | NONE | | |
| | Yellow Metal | scalar | Visual* | NONE | NONE | | |
| CONTAMINATION | Silicon | ppm | ASTM D5185(m) | >25 | 1 | | |
| The water content is negligible. There is no indication of any contamination in the oil. | Potassium | ppm | ASTM D5185(m) | | - <1 | | |
| | Water | % | ASTM D6304* | >0.1 | 0.020 | | |
| | ppm Water | ppm | ASTM D6304* | >1000 | 201 | | |
| | Silt | scalar | Visual* | NONE | NONE | | |
| | Debris | scalar | Visual* | NONE | NONE | | |
| | Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| | Appearance | scalar | Visual* | NORML | NORML | | |
| | Odor | scalar | Visual* | NORML | FREON | | |
| | Emulsified Water | scalar | Visual* | >0.1 | NEG | | |
| FLUID CONDITION | Sodium | ppm | ASTM D5185(m) | | 0 | | |
| | Boron | ppm | ASTM D5185(m) | | 0 | | |
| The AN level is acceptable for this fluid. The condition of the oil is | Barium | ppm | ASTM D5185(m) | | 0 | | |
| suitable for further service. | Molybdenum | ppm | ASTM D5185(m) | | 0 | | |
| | Manganese | ppm | ASTM D5185(m) | | 0 | | |
| | Magnesium | ppm | ASTM D5185(m) | | 0 | | |
| | Calcium | ppm | ASTM D5185(m) | | 0 | | |
| | Phosphorus | ppm | ASTM D5185(m) | | <1 | | |
| | Zinc | ppm | ASTM D5185(m) | | <1 | | |
| | Sulfur | ppm | ASTM D5185(m) | | 5 | | |
| | Acid Number (AN) | mg KOH/g | ASTM D974* | | 0.00 | | |
| | Visc @ 40°C | cSt | ASTM D7279(m) | | 38.0 | | |





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0907704 Lab Number : 02620223

Unique Number : 5737333

Received **Tested** Diagnosed : 06 Mar 2024

: 11 Mar 2024

: 11 Mar 2024 - Kevin Marson

Test Package : IND 2 (Additional Tests: KF)

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Neelands Group Limited 4131 Palladium Way

Burlington, ON CA L7M 0V9 Contact: Mike Squires mike.squires@neelands.com

T: (905)975-0794 F: (905)334-7090