

TRANSMISSION/SILVERTHORN Machine Id 75998-377 Component Coolant Fluid

CONVENTIONAL COOLANT (--- GAL)

RECOMMENDATION

The fluid is suitable for further service. Resample at the next service interval to monitor.

CORROSION

All metal levels are normal indicating no corrosion in the cooling system.

CONTAMINANTS

There is no indication of any contamination in the coolant.

.....

COOLANT CONDITION

The nitrite level is acceptable. The pH level of this fluid is within the acceptable limits. The reserve alkalinity of this fluid is acceptable.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0918899		
Sample Date		Client Info		11 Mar 2024		
Machine Age	hrs	Client Info		920		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
Iron	ppm	ASTM D5185(m)	>15	0		
Aluminum		ASTM D5185(m)	>10	4		
Copper	ppm	ASTM D5185(m)	>10	- <1		
Lead	ppm	ASTM D5185(m)	>10	0		
Tin	ppm	ASTM D5185(m)	>10	0		
Silver	ppm	ASTM D5185(m)	>10	1		
	ppm	. ,				
Zinc	ppm	ASTM D5185(m)	>10	0		
Calcium	ppm	ASTM D5185(m)	>100	2		
Magnesium	ppm	ASTM D5185(m)	>40	<1		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Coolant Appearance		Visual*	Clear	Clear		
Boiling Point	°C	WC Method*		106		
•	0	ASTM D1298*				
Specific Gravity	Scale 0-14	ASTM D1298 ASTM D1287*	9.5	1.058 9.27		
pH Nitrites		Alcan Test Kit*	9.5 1500	9.27		
Reserve Alkalinity	ppm Scale 0-20	AICan Test Kit ASTM D1121*		11.5		
	%	ASTM D1121 ASTM D3321*	8.5 50	42.8		
Percentage Glycol Freezing Point	°C	ASTM D3321*		42.0 -27		
Carboxylate	0	A31WI D3321	-40	-21		
Silicon	nom	ASTM D5185(m)		79		
Phosphorus	ppm	ASTM D5185(m)		838		
Boron	ppm	ASTM D5185(m)		030 168		
Molybdenum	ppm	ASTM D5185(m)		720		
Sodium	ppm	ASTM D5185(m)		2045		
Potassium	ppm	. /				
	ppm	ASTM D5185(m)	Creat	5647		
Coolant Color		Visual*	Green	Grn/Yellow		

Contact/Location: Transmission - Kevin Ho - MINMIS





