



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
{UNASSIGNED}
Machine Id
911039
Component
Right Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0107647	GFL0096346	GFL0087669
Sample Date		Client Info		26 Mar 2024	18 Oct 2023	26 Jul 2023
Machine Age	kms	Client Info		135737	1135239	102226
Oil Age	kms	Client Info		0	0	0
Filter Age	kms	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>120	8	11	8
Chromium	ppm	ASTM D5185(m)	>20	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>5	<1	1	<1
Titanium	ppm	ASTM D5185(m)	>2	0	0	0
Silver	ppm	ASTM D5185(m)	>2	0	<1	<1
Aluminum	ppm	ASTM D5185(m)	>20	2	4	3
Lead	ppm	ASTM D5185(m)	>40	0	<1	<1
Copper	ppm	ASTM D5185(m)	>330	<1	3	10
Tin	ppm	ASTM D5185(m)	>15	0	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION










Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>25	1	7	4
Potassium	ppm	ASTM D5185(m)	>20	2	6	4
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>4	0.3	0.5	0.2
Nitration	Abs/cm	ASTM D7624*	>20	8.0	8.1	6.8
Sulfation	Abs/.1mm	ASTM D7415*	>30	19.6	19.9	20.0
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

L'état de l'huile est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		5	10	8
Boron	ppm	ASTM D5185(m)	2	1	2	2
Barium	ppm	ASTM D5185(m)	0	0	<1	0
Molybdenum	ppm	ASTM D5185(m)	50	58	62	64
Manganese	ppm	ASTM D5185(m)	0	0	0	<1
Magnesium	ppm	ASTM D5185(m)	950	957	1007	1060
Calcium	ppm	ASTM D5185(m)	1050	1061	1081	1170
Phosphorus	ppm	ASTM D5185(m)	995	983	992	1155
Zinc	ppm	ASTM D5185(m)	1180	1172	1184	1267
Sulfur	ppm	ASTM D5185(m)	2600	2456	2375	2716
Oxidation	Abs/.1mm	ASTM D7414*	>25	15.5	15.6	14.6
Visc @ 100°C	cSt	ASTM D7279(m)	12.00	11.5	11.3	11.5



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0107647
Lab Number : 02625173
Unique Number : 5750292
Test Package : MOB 1
Received : 28 Mar 2024
Tested : 28 Mar 2024
Diagnosed : 28 Mar 2024 - Kevin Marson

GFL Environmental - 747 - GMA - Solid Waste
 4 Chemin du Tremblay,
 Boucherville, QC
 CA J4B 6Z5
 Contact: Steve Voyer
 svoyer@matrec.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: