

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

## Area [4484] Machine Id 03-027-CE Component New (Unused) Oil

## PETRO CANADA LUMINOL LS B-4 (--- GAL)

RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
	Sample Number	OOW	Client Info		PP0000927		HIStOLY2
This is a baseline read-out on the submitted sample.	Sample Number		Client Info		28 Mar 2024		
	Machine Age	hrs	Client Info		0		
	Oil Age	hrs	Client Info		0		
	Filter Age	hrs	Client Info		0		
	Oil Changed	1115	Client Info		N/A		
	Filter Changed		Client Info		N/A		
	Sample Status				NORMAL		
WEAR	Iron	ppm	ASTM D5185(m)	>5	0		
{not applicable}	Chromium	ppm	ASTM D5185(m)	>5	0		
	Nickel	ppm	ASTM D5185(m)	>5	0		
	Titanium	ppm	ASTM D5185(m)		0		
	Silver	ppm	ASTM D5185(m)	>5	0		
	Aluminum	ppm	ASTM D5185(m)	>5	0		
	Lead	ppm	ASTM D5185(m)	>5	0		
	Copper	ppm	ASTM D5185(m)	>5	0		
	Tin	ppm	ASTM D5185(m)	>5	0		
	Vanadium	ppm	ASTM D5185(m)		0		
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
CONTAMINATION	Silicon	nom	ASTM D5185(m)	>15	0		
{not applicable}	Potassium	ppm		>20	0		
	Water	ppm	WC Method	>20	NEG		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
			· · · · · · · · · · · · · · · · · · ·				
FLUID CONDITION	Sodium	ppm	ASTM D5185(m)	>5	0		
{not applicable}	Boron	ppm	ASTM D5185(m)		<1		
	Barium	ppm	ASTM D5185(m)		0		
	Molybdenum	ppm	ASTM D5185(m)		0		
	Manganese	ppm	ASTM D5185(m)		0		
	Magnesium	ppm	ASTM D5185(m)		0		
	Calcium	ppm	ASTM D5185(m)		0		
	Phosphorus	ppm	ASTM D5185(m)		0		
	Zinc	ppm	ASTM D5185(m)		<1		
	Sulfur	ppm	ASTM D5185(m)		<1		
	Visc @ 40°C	cSt	ASTM D7279(m)		9.4		
	Visc @ 100°C	cSt	ASTM D7279(m)		2.5		
		-					

Viscosity Index (VI) Scale ASTM D2270\*

Contact/Location: Mark Michalkoff - OLENIA

85



