



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR LH50M 145181-1216
Component
Transmission (Manual)
Fluid
TDTO FLUID SAE 10W (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0286805	LH0274797	LH0261382
Sample Date		Client Info		01 Apr 2024	29 Aug 2023	28 Apr 2023
Machine Age	hrs	Client Info		2092	1043	497
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>200	18	17	16
Chromium	ppm	ASTM D5185(m)	>5	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>5	0	0	<1
Titanium	ppm	ASTM D5185(m)		0	0	<1
Silver	ppm	ASTM D5185(m)	>7	0	0	0
Aluminum	ppm	ASTM D5185(m)	>25	2	2	3
Lead	ppm	ASTM D5185(m)	>45	0	<1	1
Copper	ppm	ASTM D5185(m)	>225	24	16	15
Tin	ppm	ASTM D5185(m)	>10	<1	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	<1
White Metal	scalar	Visual*	NONE	NONE	NONE	VLITE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185(m)	>125	2	4	4
Potassium	ppm	ASTM D5185(m)	>20	1	2	3
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	VLITE	VLITE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		20	30	56
Boron	ppm	ASTM D5185(m)	37	2	3	4
Barium	ppm	ASTM D5185(m)	7	<1	<1	<1
Molybdenum	ppm	ASTM D5185(m)	5	39	28	<1
Manganese	ppm	ASTM D5185(m)		16	12	12
Magnesium	ppm	ASTM D5185(m)	40	639	464	8
Calcium	ppm	ASTM D5185(m)	2650	1847	2213	3417
Phosphorus	ppm	ASTM D5185(m)	1050	1053	1106	1143
Zinc	ppm	ASTM D5185(m)	1075	1158	1173	1147
Sulfur	ppm	ASTM D5185(m)	5750	4863	5160	7366
Visc @ 40°C	cSt	ASTM D7279(m)	40	55.5	54.7	47.3



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0286805 **Received** : 02 Apr 2024
Lab Number : 02626163 **Tested** : 03 Apr 2024
Unique Number : 5759295 **Diagnosed** : 03 Apr 2024 - Kevin Marson
Test Package : MOB 1

METALOGICS INC
 70 NORTH QUEEN ST.
 ETOBICOKE, ON
 CA M8Z 2C7
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: