



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[397277]
 Machine Id

16-8808
 Component
Diesel Engine

Fluid
VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP450210	VCP394636	VCP381784
Sample Date		Client Info		23 Mar 2024	23 Aug 2023	13 Apr 2023
Machine Age	hrs	Client Info		15000	14500	13964
Oil Age	hrs	Client Info		500	500	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>200	12	13	11
Chromium	ppm	ASTM D5185(m)	>20	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>5	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	<1	<1
Silver	ppm	ASTM D5185(m)	>2	0	0	0
Aluminum	ppm	ASTM D5185(m)	>30	5	4	3
Lead	ppm	ASTM D5185(m)	>40	0	<1	<1
Copper	ppm	ASTM D5185(m)	>20	2	1	<1
Tin	ppm	ASTM D5185(m)	>20	<1	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	2	4	4
Potassium	ppm	ASTM D5185(m)	>20	<1	0	0
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>3	0.4	0.5	0.3
Nitration	Abs/cm	ASTM D7624*	>20	8.9	10.4	9.6
Sulfation	Abs/.1mm	ASTM D7415*	>30	23.5	26.0	24.4
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		4	4	3
Boron	ppm	ASTM D5185(m)	2.5	35	30	36
Barium	ppm	ASTM D5185(m)	0.0	0	0	0
Molybdenum	ppm	ASTM D5185(m)	0.7	39	40	48
Manganese	ppm	ASTM D5185(m)	0.0	<1	<1	<1
Magnesium	ppm	ASTM D5185(m)	256	485	501	652
Calcium	ppm	ASTM D5185(m)	2057	1875	1874	1875
Phosphorus	ppm	ASTM D5185(m)	935	969	1054	1097
Zinc	ppm	ASTM D5185(m)	1223	1151	1182	1227
Sulfur	ppm	ASTM D5185(m)	4079	2542	2596	2570
Oxidation	Abs/.1mm	ASTM D7414*	>25	21.3	23.4	23.2
Visc @ 100°C	cSt	ASTM D7279(m)	15.0	13.4	14.1	13.8



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : VCP450210
Lab Number : 02627842
Unique Number : 5760974
Test Package : MOB 1

CRH CANADA GROUP INC.
 P.O. BOX 5400
 CONCORD, ON
 CA L4K 1B6
 Contact: Dan Brown
 dan.brown@ca.crh.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.