

Area
MICHAUDVILLE
Machine Id
1209
Component
Transmission (Auto)
Fluid
DEXRON III (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DEXRON III. Please confirm.
Please specify the component make and model with your next sample.

WEAR

All component wear rates are normal.











CONTAMINATION

There is no indication of any contamination in the fluid.

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------------|--------|---------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | PC0083764 | PC0071967 | PC0065077 |
| Sample Date | | Client Info | | 14 Apr 2024 | 21 Feb 2023 | 28 Sep 2022 |
| Machine Age | kms | Client Info | | 17826 | 16531 | 15994 |
| Oil Age | kms | Client Info | | 0 | 0 | 0 |
| Filter Age | kms | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | N/A | N/A |
| Filter Changed | | Client Info | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |
| Iron | ppm | ASTM D5185(m) | >160 | 30 | 147 | 128 |
| Chromium | ppm | ASTM D5185(m) | >5 | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185(m) | >5 | 0 | 0 | 0 |
| Titanium | ppm | ASTM D5185(m) | | 0 | <1 | 0 |
| Silver | ppm | ASTM D5185(m) | >5 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185(m) | >50 | 6 | 26 | 24 |
| Lead | ppm | ASTM D5185(m) | >50 | <1 | 12 | 11 |
| Copper | ppm | ASTM D5185(m) | >225 | 6 | 36 | 32 |
| Tin | ppm | ASTM D5185(m) | >10 | 0 | 2 | 2 |
| Vanadium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| White Metal | scalar | Visual* | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | Visual* | NONE | NONE | NONE | NONE |
| Silicon | ppm | ASTM D5185(m) | >20 | 4 | 9 | 8 |
| Potassium | ppm | ASTM D5185(m) | >20 | <1 | <1 | <1 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| Silt | scalar | Visual* | NONE | NONE | NONE | NONE |
| Debris | scalar | Visual* | NONE | VLITE | VLITE | NONE |
| Sand/Dirt | scalar | Visual* | NONE | VLITE | NONE | NONE |
| Appearance | scalar | Visual* | NORML | NORML | NORML | NORML |
| Odor | scalar | Visual* | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | Visual* | >0.1 | NEG | NEG | NEG |
| Sodium | ppm | ASTM D5185(m) | | 2 | 6 | 6 |
| Boron | ppm | ASTM D5185(m) | | 81 | 146 | 144 |
| Barium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185(m) | | <1 | 1 | 1 |
| Magnesium | ppm | ASTM D5185(m) | | 3 | <1 | <1 |
| Calcium | ppm | ASTM D5185(m) | | 123 | 86 | 85 |
| Phosphorus | ppm | ASTM D5185(m) | | 226 | 392 | 383 |
| Zinc | ppm | ASTM D5185(m) | | 5 | 4 | 5 |
| Sulfur | ppm | ASTM D5185(m) | | 1417 | 1417 | 1389 |
| Visc @ 40°C | cSt | ASTM D7279(m) | 26.0 | 34.2 | 36.0 | 36.2 |
| Visc @ 100°C | cSt | ASTM D7279(m) | 5.5 | 6.7 | 7 | 7.1 |
| Viscosity Index (VI) | Scale | ASTM D2270* | 155 | 156 | 159 | 162 |



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0083764
Lab Number : 02628920
Unique Number : 5762052
Test Package : MOB 1 (Additional Tests: KV100, VI)

LES ENTREPRISES MICHAUVILLE INC.
 270 RUE BRUNET
 MONT ST-HILAIRE, QC
 CA J3H 0M6
 Contact: Martin Trudel
 mtrudel@michaudville.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: