



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
146
 Component
Rear Transmission (Auto)
 Fluid
CASTROL TRANSYND (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0888994	WC0866601	WC0866561
Sample Date		Client Info		05 Apr 2024	11 Dec 2023	23 Oct 2023
Machine Age	kms	Client Info		0	0	0
Oil Age	kms	Client Info		18305	47481	38029
Filter Age	kms	Client Info		18305	47481	38029
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ATTENTION	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>230	39	57	52
Chromium	ppm	ASTM D5185(m)	>2	0	0	0
Nickel	ppm	ASTM D5185(m)	>5	0	<1	<1
Titanium	ppm	ASTM D5185(m)	>2	0	0	0
Silver	ppm	ASTM D5185(m)	>5	0	<1	<1
Aluminum	ppm	ASTM D5185(m)	>65	29	42	35
Lead	ppm	ASTM D5185(m)	>55	4	8	5
Copper	ppm	ASTM D5185(m)	>85	8	12	11
Tin	ppm	ASTM D5185(m)	>5	1	2	2
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185(m)	>20	5	8	8
Potassium	ppm	ASTM D5185(m)	>20	2	5	3
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	VLITE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

Sodium	ppm	ASTM D5185(m)		4	8	7
Boron	ppm	ASTM D5185(m)	150	60	52	54
Barium	ppm	ASTM D5185(m)	0	0	<1	<1
Molybdenum	ppm	ASTM D5185(m)	0	4	0	0
Manganese	ppm	ASTM D5185(m)		<1	<1	<1
Magnesium	ppm	ASTM D5185(m)	0	1	2	2
Calcium	ppm	ASTM D5185(m)	40	125	98	100
Phosphorus	ppm	ASTM D5185(m)	320	223	226	232
Zinc	ppm	ASTM D5185(m)	5	8	10	9
Sulfur	ppm	ASTM D5185(m)	1050	1250	1027	1031
Acid Number (AN)	mg KOH/g	ASTM D974*	1.0	1.18	1.41	---
Visc @ 40°C	cSt	ASTM D7279(m)	38.9	33.9	34.7	35.0
Visc @ 100°C	cSt	ASTM D7279(m)	7.3	6.6	6.8	6.9
Viscosity Index (VI)	Scale	ASTM D2270*	168	153	158	161



ISO 17025:2017
Accredited
Laboratory

Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0888994
Lab Number : 02628925
Unique Number : 5762057
Test Package : MOB 2 (Additional Tests: KV100, TAN Man, VI)

Received : 15 Apr 2024
Tested : 16 Apr 2024
Diagnosed : 16 Apr 2024 - Wes Davis

CITY OF THUNDER BAY
 AUTO MAINTENANCE STORES, 570 FORT WILLIAM ROAD
 THUNDER BAY, ON
 CA P7B 2Z8
 Contact: Sean Malcolm
 sean.malcolm@thunderbay.ca
 T: (807)684-2716
 F: (807)344-0237

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.