



VOLVO

OIL ANALYSIS REPORT

| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |



Area
[400402]
Machine Id
16-8112
Component
Rear Axle
Fluid
VOLVO WB 102 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | VCP394285 | VCP380508 | VCP380234 |
| Sample Date | | Client Info | | 10 Apr 2024 | 25 Oct 2023 | 18 Jun 2023 |
| Machine Age | hrs | Client Info | | 10000 | 9000 | 8010 |
| Oil Age | hrs | Client Info | | 2000 | 1000 | 4000 |
| Filter Age | hrs | Client Info | | 0 | 0 | 4000 |
| Oil Changed | | Client Info | | Not Changed | Changed | Changed |
| Filter Changed | | Client Info | | Not Changed | Changed | Changed |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|---------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185(m) | >500 | 24 | 16 | 84 |
| Chromium | ppm | ASTM D5185(m) | >20 | <1 | 0 | 2 |
| Nickel | ppm | ASTM D5185(m) | >10 | 0 | <1 | <1 |
| Titanium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185(m) | | 0 | <1 | <1 |
| Aluminum | ppm | ASTM D5185(m) | >30 | 1 | 2 | 2 |
| Lead | ppm | ASTM D5185(m) | >50 | 0 | 0 | <1 |
| Copper | ppm | ASTM D5185(m) | >120 | <1 | <1 | 2 |
| Tin | ppm | ASTM D5185(m) | >20 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| White Metal | scalar | Visual* | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | Visual* | NONE | NONE | NONE | NONE |

CONTAMINATION










There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|---------------|-------|--------------|-------|-------|
| Silicon | ppm | ASTM D5185(m) | >50 | 11 | 13 | 8 |
| Potassium | ppm | ASTM D5185(m) | >20 | 0 | 0 | 1 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Silt | scalar | Visual* | NONE | NONE | NONE | NONE |
| Debris | scalar | Visual* | NONE | NONE | NONE | VLITE |
| Sand/Dirt | scalar | Visual* | NONE | NONE | NONE | NONE |
| Appearance | scalar | Visual* | NORML | NORML | NORML | NORML |
| Odor | scalar | Visual* | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | Visual* | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|-------------|-----|---------------|--|--------------|------|------|
| Sodium | ppm | ASTM D5185(m) | | 1 | <1 | 8 |
| Boron | ppm | ASTM D5185(m) | | 106 | 120 | 95 |
| Barium | ppm | ASTM D5185(m) | | 0 | <1 | 0 |
| Molybdenum | ppm | ASTM D5185(m) | | 0 | 0 | 1 |
| Manganese | ppm | ASTM D5185(m) | | <1 | 0 | 2 |
| Magnesium | ppm | ASTM D5185(m) | | 14 | 14 | 12 |
| Calcium | ppm | ASTM D5185(m) | | 3579 | 4158 | 3319 |
| Phosphorus | ppm | ASTM D5185(m) | | 1187 | 1352 | 1269 |
| Zinc | ppm | ASTM D5185(m) | | 1437 | 1594 | 1398 |
| Sulfur | ppm | ASTM D5185(m) | | 3204 | 3257 | 3160 |
| Visc @ 40°C | cSt | ASTM D7279(m) | | 41.9 | 43.6 | 38.9 |



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : VCP394285 **Received** : 17 Apr 2024
Lab Number : 02629777 **Tested** : 18 Apr 2024
Unique Number : 5762909 **Diagnosed** : 18 Apr 2024 - Wes Davis
Test Package : MOB 1

CRH CANADA GROUP INC.
 P.O. BOX 5400
 CONCORD, ON
 CA L4K 1B6
 Contact: Dan Brown
 dan.brown@ca.crh.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.