



Machine Id
412020
Component
Diesel Engine
Fluid
PETRO CANADA 10W30 (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PC0088250	PC0083849	PC0077972
Sample Date		Client Info		15 Apr 2024	14 Feb 2024	25 Oct 2023
Machine Age	kms	Client Info		178591	175031	155238
Oil Age	kms	Client Info		0	0	0
Filter Age	kms	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>120	5	13	18
Chromium	ppm	ASTM D5185(m)	>20	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>5	<1	<1	1
Titanium	ppm	ASTM D5185(m)	>2	0	0	0
Silver	ppm	ASTM D5185(m)	>2	0	0	<1
Aluminum	ppm	ASTM D5185(m)	>20	1	2	2
Lead	ppm	ASTM D5185(m)	>40	<1	1	1
Copper	ppm	ASTM D5185(m)	>330	20	4	3
Tin	ppm	ASTM D5185(m)	>15	0	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION












Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>25	1	4	5
Potassium	ppm	ASTM D5185(m)	>20	1	3	3
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>4	0	0.3	0.5
Nitration	Abs/cm	ASTM D7624*	>20	6.1	9.5	10.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	18.3	19.6	20.8
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

L'état de l'huile est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		1	2	2
Boron	ppm	ASTM D5185(m)		11	6	4
Barium	ppm	ASTM D5185(m)		0	0	<1
Molybdenum	ppm	ASTM D5185(m)		58	60	63
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)		934	949	977
Calcium	ppm	ASTM D5185(m)		1018	1177	1102
Phosphorus	ppm	ASTM D5185(m)		972	1025	1003
Zinc	ppm	ASTM D5185(m)		1126	1197	1209
Sulfur	ppm	ASTM D5185(m)		2554	2669	2396
Oxidation	Abs/.1mm	ASTM D7414*	>25	13.6	15.9	17.0
Visc @ 40°C	cSt	ASTM D7279(m)		71.7	70.0	74.1
Visc @ 100°C	cSt	ASTM D7279(m)		11.1	10.9	11.3
Viscosity Index (VI)	Scale	ASTM D2270*		145	145	144



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0088250
Lab Number : 02629908
Unique Number : 5763040
Test Package : MOB 1 (Additional Tests: KV40, VI)

GFL Environmental - 737 - Quebec City Hauling
 6205 Boul. Wilfrid Hamel,
 Quebec City, QC
 CA G2E 5G8
 Contact: Dave Beaulieu
 davebeaulieu@matrec.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: