

Machine Id
4659
Component
Transmission (Auto)
Fluid
DEXRON III (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Le fluide n'était pas spécifié, toutefois, une comparaison avec d'autres fluides indique que ce fluide est du (GENERIC) DEXRON III. Veuillez confirmer.

WEAR

Les taux d'usure de tous les composants sont normaux.










CONTAMINATION

Il n'y a aucun indice de contamination dans le fluide.

FLUID CONDITION

L'état de le fluide est acceptable pour la durée de service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0117063	GFL0097426	GFL0089660
Sample Date		Client Info		16 Apr 2024	04 Dec 2023	21 Aug 2023
Machine Age	hrs	Client Info		20284	19675	19089
Oil Age	hrs	Client Info		316	19089	18476
Filter Age	hrs	Client Info		316	19089	18476
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL
Iron	ppm	ASTM D5185(m)	>160	19	▲ 162	137
Chromium	ppm	ASTM D5185(m)	>5	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>5	0	<1	0
Titanium	ppm	ASTM D5185(m)		0	0	<1
Silver	ppm	ASTM D5185(m)	>5	0	<1	<1
Aluminum	ppm	ASTM D5185(m)	>50	4	45	43
Lead	ppm	ASTM D5185(m)	>50	<1	22	22
Copper	ppm	ASTM D5185(m)	>225	4	38	27
Tin	ppm	ASTM D5185(m)	>10	0	8	8
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Silicon	ppm	ASTM D5185(m)	>20	4	17	15
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	2
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	VLITE	NONE	VLITE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG
Sodium	ppm	ASTM D5185(m)		3	42	42
Boron	ppm	ASTM D5185(m)		74	75	77
Barium	ppm	ASTM D5185(m)		0	0	0
Molybdenum	ppm	ASTM D5185(m)		2	0	0
Manganese	ppm	ASTM D5185(m)		<1	1	1
Magnesium	ppm	ASTM D5185(m)		1	4	1
Calcium	ppm	ASTM D5185(m)		133	53	46
Phosphorus	ppm	ASTM D5185(m)		216	234	248
Zinc	ppm	ASTM D5185(m)		7	29	10
Sulfur	ppm	ASTM D5185(m)		1523	469	389
Visc @ 40°C	cSt	ASTM D7279(m)	26.0	32.1	33.3	33.5



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0117063
Lab Number : 02629977
Unique Number : 5763109
Test Package : MOB 1
Received : 18 Apr 2024
Tested : 18 Apr 2024
Diagnosed : 18 Apr 2024 - Wes Davis

GFL Environmental - 732 - Beauce - Hauling - Solid Waste
 139, 181 Street,
 Beauceville, QC
 CA G5X 2S9
 Contact: Denis Bedard

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T: (418)774-5275
 F: