



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
(C-GUGB)
Machine Id
[C-GUGB] CESSNA 172S L-30988-51A
Component
Front Piston Aircraft Engine
Fluid
SHELL AEROSHELL W 15W50 MGR (8 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0743833	WC0858920	WC0858917
Sample Date		Client Info		10 Apr 2024	15 Mar 2024	13 Feb 2024
TSN	hrs	Client Info		0	0	0
TSO	hrs	Client Info		3111	3062	3014
Oil Age	hrs	Client Info		49	48	65
Filter Age	hrs	Client Info		49	48	65
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>90	14	14	16
Chromium	ppm	ASTM D5185(m)	>20	2	2	2
Nickel	ppm	ASTM D5185(m)	>15	3	3	3
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>5	0	0	0
Aluminum	ppm	ASTM D5185(m)	>25	3	3	5
Lead	ppm	ASTM D5185(m)	>20000	3514	4267	4085
Copper	ppm	ASTM D5185(m)	>25	7	7	6
Tin	ppm	ASTM D5185(m)	>30	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>15	4	4	6
Potassium	ppm	ASTM D5185(m)	>20	0	0	<1
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Silt	scalar	Visual*	NONE	VLITE	NONE	VLITE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	.2%

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<1	<1	<1
Boron	ppm	ASTM D5185(m)		<1	0	0
Barium	ppm	ASTM D5185(m)		0	0	0
Molybdenum	ppm	ASTM D5185(m)	5	0	0	0
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)	10	<1	1	<1
Calcium	ppm	ASTM D5185(m)	10	<1	2	<1
Phosphorus	ppm	ASTM D5185(m)	1280	1110	1150	1175
Zinc	ppm	ASTM D5185(m)	10	4	6	4
Sulfur	ppm	ASTM D5185(m)	1800	1334	1386	1557
Visc @ 100°C	cSt	ASTM D7279(m)	18.2	18.5	18.7	18.4



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0743833
Lab Number : 02630175
Unique Number : 5763307
Test Package : AVI 1
Received : 19 Apr 2024
Tested : 19 Apr 2024
Diagnosed : 19 Apr 2024 - Kevin Marson

CANADIAN FLIGHT ACADEMY
 1250 AIRPORT BOULEVARD
 OSHAWA, ON
 CA L1J 8P5
 Contact: John Bayes
 bayesjohn@torontoairways.com
 T: (905)404-9252
 F: (905)404-8294

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.