WEAR CONTAMINATION FLUID CONDITION

Limit/Abn | Current

UOM

Method

NORMAL NORMAL

History1

History2

Area

[GH-9162A] 170831 DB

Unknown Component

RECOMMENDATION

{not provided} (--- GAL)

TIESOMMENDATION		00			Guilont	, .	
Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please	Sample Number		Client Info		PP		
	Sample Date		Client Info		18 Apr 2024		
	Machine Age	hrs	Client Info		0		
	Oil Age	hrs	Client Info		0		
	Filter Age	hrs	Client Info		0		
provide information regarding reservoir capacity, filter type and micron rating with	Oil Changed		Client Info		N/A		
next sample. Please specify the brand, type, and viscosity of the oil on your next sample. Please provide more complete information on your next sample.	Filter Changed		Client Info		N/A		
	Sample Status				NORMAL		
WEAR	PQ		ASTM D8184*		0		
Component wear rates appear to be normal (unconfirmed).	Iron	ppm	ASTM D5185(m)		6		
	Chromium	ppm	ASTM D5185(m)		0		
	Nickel	ppm	ASTM D5185(m)		0		
	Titanium	ppm	ASTM D5185(m)		0		
	Silver	ppm	ASTM D5185(m)		0		
	Aluminum	ppm	ASTM D5185(m)		0		
	Lead	ppm	ASTM D5185(m)		<1		
	Copper	ppm	ASTM D5185(m)		7		
	Tin	ppm	ASTM D5185(m)		0		
	Vanadium	ppm	ASTM D5185(m)		0		
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
CONTAMINATION	Silicon	ppm	ASTM D5185(m)		<1		
	Potassium	ppm	ASTM D5185(m)	>20	<1		
The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.	Water		WC Method		NEG		
	Particles >4µm		ASTM D7647	>5000	253		
	Particles >6µm		ASTM D7647		61		
	Particles >14µm		ASTM D7647	>160	3		
	Particles >21µm		ASTM D7647	>40	2		
	Particles >38µm		ASTM D7647		1		
	Particles >71µm		ASTM D7647		1		
	Oil Cleanliness		ISO 4406 (c)		15/13/9		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water		Visual*	INOTHINE	NEG		
	Linuisilied Water	Scalai			NLG		
FLUID CONDITION Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The AN level is acceptable for this fluid. The condition of the sample is suitable for further service.	Sodium	ppm	ASTM D5185(m)		<1		
	Boron	ppm	ASTM D5185(m)		<1		
	Barium	ppm	ASTM D5185(m)		0		
	Molybdenum	ppm	ASTM D5185(m)		0		
	Manganese	ppm	ASTM D5185(m)		0		
	Magnesium	ppm	ASTM D5185(m)		6		
	Calcium	ppm	ASTM D5185(m)		42		
	Phosphorus	ppm	ASTM D5185(m)		221		
	Zinc	ppm	ASTM D5105(III) ASTM D5185(m)		249		
	Sulfur	ppm	ASTM D5105(III) ASTM D5185(m)		2559		
	Acid Number (AN)	mg KOH/g	ASTM D3103(III) ASTM D974*		0.30		
	Visc @ 40°C	cSt	ASTM D7279(m)		33.4		
	V130 @ 40 0	601	MOTIVI D1213(III)		33.4		

Test





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : PP

: 02630194 Unique Number : 5763326

Received **Tested**

: 19 Apr 2024 Diagnosed Test Package: IND 2 (Additional Tests: PQ, PRTCOUNT)

: 23 Apr 2024 : 23 Apr 2024 - Kevin Marson

HIBERNIA MGMT & DEVELOPMENT CO. LTD SUITE 1000,, 100 NEW GOWER STREET ST.JOHNS, NL **CA A1C 6K3**

Contact: Sam Nash samantha.m.nash@exxonmobil.com T:

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Contact/Location: Sam Nash - HIBSTJ