

Area
MICHAUDVILLE [P-28636]

Machine Id
1501
Component
Transmission (Manual)
Fluid
{not provided} (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

WEAR

All component wear rates are normal.











CONTAMINATION

There is no indication of any contamination in the fluid.

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PC0083195	PC0077365	PC0071538
Sample Date		Client Info		23 Apr 2024	25 Jul 2023	14 Mar 2023
Machine Age	hrs	Client Info		14631	14216	13708
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL
Iron	ppm	ASTM D5185(m)	>200	127	▲ 239	197
Chromium	ppm	ASTM D5185(m)	>5	<1	1	1
Nickel	ppm	ASTM D5185(m)	>5	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	<1	<1
Silver	ppm	ASTM D5185(m)	>7	0	0	0
Aluminum	ppm	ASTM D5185(m)	>25	2	4	4
Lead	ppm	ASTM D5185(m)	>45	1	7	6
Copper	ppm	ASTM D5185(m)	>225	31	91	80
Tin	ppm	ASTM D5185(m)	>10	<1	2	2
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	VLITE	NONE	VLITE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Silicon	ppm	ASTM D5185(m)	>125	5	8	6
Potassium	ppm	ASTM D5185(m)	>20	<1	2	2
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	VLITE	VLITE
Debris	scalar	Visual*	NONE	NONE	VLITE	VLITE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG
Sodium	ppm	ASTM D5185(m)		2	5	9
Boron	ppm	ASTM D5185(m)		258	233	239
Barium	ppm	ASTM D5185(m)		0	<1	0
Molybdenum	ppm	ASTM D5185(m)		0	<1	1
Manganese	ppm	ASTM D5185(m)		2	6	6
Magnesium	ppm	ASTM D5185(m)		1	3	3
Calcium	ppm	ASTM D5185(m)		46	54	54
Phosphorus	ppm	ASTM D5185(m)		1117	1168	1195
Zinc	ppm	ASTM D5185(m)		15	65	61
Sulfur	ppm	ASTM D5185(m)		366	418	438
Visc @ 40°C	cSt	ASTM D7279(m)		95.8	94.5	95.3
Visc @ 100°C	cSt	ASTM D7279(m)		14.7	14.6	14.5
Viscosity Index (VI)	Scale	ASTM D2270*		160	160	157



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PC0083195
Lab Number : 02631203
Unique Number : 5772356
Test Package : MOB 1 (Additional Tests: KV100, VI)
Received : 24 Apr 2024
Tested : 24 Apr 2024
Diagnosed : 24 Apr 2024 - Wes Davis

LES ENTREPRISES MICHAUVILLE INC.
 270 RUE BRUNET
 MONT ST-HILAIRE, QC
 CA J3H 0M6
 Contact: Martin Trudel
 mtrudel@michaudville.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.