



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[8-397993]

Machine Id
16-8017

Component
Diesel Engine

Fluid
VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP449348	VCP394321	VCP392267
Sample Date		Client Info		21 Mar 2024	20 Dec 2023	05 Oct 2023
Machine Age	hrs	Client Info		9578	9021	8523
Oil Age	hrs	Client Info		500	1000	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>100	6	6	5
Chromium	ppm	ASTM D5185(m)	>10	0	0	0
Nickel	ppm	ASTM D5185(m)	>10	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>2	0	0	<1
Aluminum	ppm	ASTM D5185(m)	>10	1	1	1
Lead	ppm	ASTM D5185(m)	>20	0	<1	<1
Copper	ppm	ASTM D5185(m)	>15	<1	<1	<1
Tin	ppm	ASTM D5185(m)	>10	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	2	3	4
Potassium	ppm	ASTM D5185(m)	>20	<1	1	16
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	0.0
Soot %	%	ASTM D7844*	>3	0	0	0
Nitration	Abs/cm	ASTM D7624*	>20	7.5	7.7	7.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	22.0	22.2	22.4
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		2	3	2
Boron	ppm	ASTM D5185(m)	2.5	42	36	30
Barium	ppm	ASTM D5185(m)	0.0	0	0	0
Molybdenum	ppm	ASTM D5185(m)	0.7	40	38	40
Manganese	ppm	ASTM D5185(m)	0.0	<1	0	0
Magnesium	ppm	ASTM D5185(m)	256	507	489	504
Calcium	ppm	ASTM D5185(m)	2057	1708	1674	1710
Phosphorus	ppm	ASTM D5185(m)	935	923	900	924
Zinc	ppm	ASTM D5185(m)	1223	1081	1036	1095
Sulfur	ppm	ASTM D5185(m)	4079	2393	2496	2435
Oxidation	Abs/.1mm	ASTM D7414*	>25	20.1	20.5	20.2
Visc @ 100°C	cSt	ASTM D7279(m)	15.0	12.4	12.2	12.7



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : VCP449348
Lab Number : 02632221
Unique Number : 5773374
Test Package : MOB 1

Received : 30 Apr 2024
Tested : 30 Apr 2024
Diagnosed : 30 Apr 2024 - Wes Davis

CRH CANADA GROUP INC.
P.O. BOX 5400
CONCORD, ON
CA L4K 1B6
Contact: Dan Brown
dan.brown@ca.crh.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
Validity of results and interpretation are based on the sample and information as supplied.

T:
F: