



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
810000
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0107330	GFL0107282	GFL0079256
Sample Date		Client Info		01 May 2024	28 Feb 2024	07 Nov 2023
Machine Age	hrs	Client Info		9607	9178	600
Oil Age	hrs	Client Info		600	600	600
Filter Age	hrs	Client Info		600	600	600
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>80	20	32	26
Chromium	ppm	ASTM D5185(m)	>5	<1	2	2
Nickel	ppm	ASTM D5185(m)	>2	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>3	0	<1	<1
Aluminum	ppm	ASTM D5185(m)	>30	2	4	4
Lead	ppm	ASTM D5185(m)	>30	0	<1	0
Copper	ppm	ASTM D5185(m)	>150	2	3	2
Tin	ppm	ASTM D5185(m)	>5	0	<1	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	NONE	---	---

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	6	11	11
Potassium	ppm	ASTM D5185(m)	>20	<1	2	<1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>3	0.3	0.5	0.3
Nitration	Abs/cm	ASTM D7624*	>20	8.3	9.5	6.6
Sulfation	Abs/.1mm	ASTM D7415*	>30	19.6	21.0	19.3
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		6	8	6
Boron	ppm	ASTM D5185(m)	0	4	1	2
Barium	ppm	ASTM D5185(m)	0	0	0	<1
Molybdenum	ppm	ASTM D5185(m)	60	62	62	60
Manganese	ppm	ASTM D5185(m)	0	<1	0	0
Magnesium	ppm	ASTM D5185(m)	1010	1018	1013	969
Calcium	ppm	ASTM D5185(m)	1070	1053	1124	1061
Phosphorus	ppm	ASTM D5185(m)	1150	997	1021	973
Zinc	ppm	ASTM D5185(m)	1270	1202	1240	1190
Sulfur	ppm	ASTM D5185(m)	2060	2372	2496	2457
Oxidation	Abs/.1mm	ASTM D7414*	>25	16.2	18.2	14.7
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	14.4	14.1	14.5



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0107330
Lab Number : 02632732
Unique Number : 5773885
Test Package : MOB 1 (Additional Tests: Visual)
Received : 02 May 2024
Tested : 02 May 2024
Diagnosed : 02 May 2024 - Wes Davis

GFL Environmental - 250 - Sault Ste Marie Hauling + MRF
 86 Sackville Rd,
 Sault Ste. Marie, ON
 CA P6B 4T6
 Contact: Mike Pelletier
 mpelletier@gflenv.com
 T: (705)945-7554
 F: (705)945-7857

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.