



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR LH26M 124532-1252

Component
Swing Drive

Fluid
PETRO CANADA TRAXON 75W90 SYNTHETIC (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0288067	LH0181020	LH0181007
Sample Date		Client Info		22 Apr 2024	08 Sep 2023	10 Jan 2023
Machine Age	hrs	Client Info		5135	4078	3035
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		None	None	None
Sample Status				NORMAL	ABNORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>350	203	▲ 357	▲ 544
Chromium	ppm	ASTM D5185(m)	>15	2	3	3
Nickel	ppm	ASTM D5185(m)	>5	0	0	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	<1	0
Aluminum	ppm	ASTM D5185(m)	>5	0	<1	<1
Lead	ppm	ASTM D5185(m)	>10	0	2	2
Copper	ppm	ASTM D5185(m)	>300	37	72	75
Tin	ppm	ASTM D5185(m)	>15	0	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>15	2	2	3
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	<1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	▲ .2%

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<1	1	2
Boron	ppm	ASTM D5185(m)	328	287	268	218
Barium	ppm	ASTM D5185(m)	1	0	0	0
Molybdenum	ppm	ASTM D5185(m)		0	<1	<1
Manganese	ppm	ASTM D5185(m)		1	2	4
Magnesium	ppm	ASTM D5185(m)	1	2	2	3
Calcium	ppm	ASTM D5185(m)	7	24	22	21
Phosphorus	ppm	ASTM D5185(m)	1145	1225	1283	1325
Zinc	ppm	ASTM D5185(m)	3	10	15	27
Sulfur	ppm	ASTM D5185(m)	17909	19990	20632	22100
Visc @ 40°C	cSt	ASTM D7279(m)	99.6	103	103	98.2



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0288067
Lab Number : 02632850
Unique Number : 5774003
Test Package : MOB 1
Received : 02 May 2024
Tested : 02 May 2024
Diagnosed : 02 May 2024 - Wes Davis

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

Amix Recycling
 11698 140 Street
 Surrey, BC
 CA V3R 2V4
 Contact: Kenji Wong
 kwong@amixgroup.ca
 T:
 F: (250)802-1002