



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR LH50M 138820-1216
Component
Front Left Wheel Hub
Fluid
GEAR OIL SAE 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH	LH	LH0260715
Sample Date		Client Info		01 May 2024	11 Dec 2023	26 May 2023
Machine Age	hrs	Client Info		1000	2140	950
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Filter Changed		Client Info		None	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>325	109	56	34
Chromium	ppm	ASTM D5185(m)	>3	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	0	<1	0
Titanium	ppm	ASTM D5185(m)		0	0	<1
Silver	ppm	ASTM D5185(m)		0	<1	0
Aluminum	ppm	ASTM D5185(m)	>10	4	2	2
Lead	ppm	ASTM D5185(m)	>4	<1	2	<1
Copper	ppm	ASTM D5185(m)	>75	27	46	26
Tin	ppm	ASTM D5185(m)	>3	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	VLITE	NONE	LIGHT
Yellow Metal	scalar	Visual*	NONE	NONE	VLITE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>75	25	8	7
Potassium	ppm	ASTM D5185(m)	>20	2	<1	2
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	VLITE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	VLITE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>170	10	9	7
Boron	ppm	ASTM D5185(m)	400	3	4	10
Barium	ppm	ASTM D5185(m)	200	0	<1	0
Molybdenum	ppm	ASTM D5185(m)	12	0	0	<1
Manganese	ppm	ASTM D5185(m)		3	3	3
Magnesium	ppm	ASTM D5185(m)	12	2	1	<1
Calcium	ppm	ASTM D5185(m)	150	31	41	85
Phosphorus	ppm	ASTM D5185(m)	1650	2442	2642	3901
Zinc	ppm	ASTM D5185(m)	125	35	54	35
Sulfur	ppm	ASTM D5185(m)	22500	24405	25475	22267
Visc @ 40°C	cSt	ASTM D7279(m)	143	175	171	143



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH **Received** : 02 May 2024
Lab Number : 02632863 **Tested** : 02 May 2024
Unique Number : 5774016 **Diagnosed** : 02 May 2024 - Wes Davis
Test Package : MOB 1

D.P. Metal Inc.
 373A Chemin Grande-Ligne
 Saint-Urbain Premier, QC
 CA J0S 1Y0
 Contact: Service .

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T: (450)427-0506
 F: