



Machine Id  
**910077**  
Component  
**Diesel Engine**  
Fluid  
**CASTROL TECTION EXTRA SAE 15W-40 (42 LTR)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0118910</b>	GFL0094456	GFL0094378
Sample Date		Client Info		<b>07 May 2024</b>	21 Feb 2024	30 Nov 2023
Machine Age	hrs	Client Info		<b>7615</b>	6994	6435
Oil Age	hrs	Client Info		<b>7615</b>	6994	0
Filter Age	hrs	Client Info		<b>7615</b>	6994	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>120	<b>13</b>	13	10
Chromium	ppm	ASTM D5185(m)	>20	<b>0</b>	<1	0
Nickel	ppm	ASTM D5185(m)	>5	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185(m)	>2	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185(m)	>20	<b>3</b>	4	3
Lead	ppm	ASTM D5185(m)	>40	<b>2</b>	1	<1
Copper	ppm	ASTM D5185(m)	>330	<b>2</b>	4	2
Tin	ppm	ASTM D5185(m)	>15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0

### CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>25	<b>2</b>	5	3
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	2	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	ASTM D7844*	>4	<b>0.4</b>	0.5	0.4
Nitration	Abs/cm	ASTM D7624*	>20	<b>9.6</b>	10.7	10.1
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>22.4</b>	22.1	20.6
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<b>4</b>	4	3
Boron	ppm	ASTM D5185(m)	30	<b>17</b>	23	28
Barium	ppm	ASTM D5185(m)		<b>0</b>	0	<1
Molybdenum	ppm	ASTM D5185(m)		<b>83</b>	86	87
Manganese	ppm	ASTM D5185(m)		<b>&lt;1</b>	0	0
Magnesium	ppm	ASTM D5185(m)	110	<b>320</b>	152	124
Calcium	ppm	ASTM D5185(m)	2740	<b>1938</b>	2065	2075
Phosphorus	ppm	ASTM D5185(m)	1240	<b>997</b>	961	932
Zinc	ppm	ASTM D5185(m)	1350	<b>1179</b>	1153	1152
Sulfur	ppm	ASTM D5185(m)	3520	<b>2737</b>	2884	2762
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>17.0</b>	16.8	15.4
Visc @ 100°C	cSt	ASTM D7279(m)	15.2	<b>14.3</b>	14.0	13.6



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0118910  
**Lab Number** : 02634058  
**Unique Number** : 5775211  
**Test Package** : MOB 1

**GFL Environmental - 222 - Sandhill**  
 SANDHILL DISPOSAL & RECYCLING DIVIS, 19 COMMERCE ROAD  
 ORANGEVILLE, ON  
 CA L9W 3X5  
 Contact: GLENN COOK  
 gcook@gflenv.com  
 T: (519)940-4167  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.