



# LIEBHERR

## OIL ANALYSIS REPORT



Area

**(353690)**

Machine Id

**LIEBHERR LH60M 131944-1475**

Component

**Front Left Wheel Hub**

Fluid

**PETRO CANADA TRAXON 75W90 SYNTHETIC (1 LTR)**

WEAR

NORMAL

CONTAMINATION

NORMAL

FLUID CONDITION

NORMAL

### RECOMMENDATION

Resample at the next service interval to monitor.

### WEAR

All component wear rates are normal.

### CONTAMINATION

There is no indication of any contamination in the oil.

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.










Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LH0288318</b>	LH0281360	LH0276950
Sample Date		Client Info		<b>27 Apr 2024</b>	27 Jan 2024	22 Nov 2023
Machine Age	hrs	Client Info		<b>12400</b>	11193	10354
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

Iron	ppm	ASTM D5185(m)	>650	<b>252</b>	177	69
Chromium	ppm	ASTM D5185(m)	>4	<b>2</b>	1	<1
Nickel	ppm	ASTM D5185(m)	>4	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185(m)	>4	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185(m)		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>25	<b>5</b>	1	<1
Lead	ppm	ASTM D5185(m)	>4	<b>0</b>	0	0
Copper	ppm	ASTM D5185(m)	>60	<b>3</b>	3	2
Tin	ppm	ASTM D5185(m)	>4	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
White Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	LIGHT
Yellow Metal	scalar	Visual*	NONE	<b>LIGHT</b>	NONE	NONE

Silicon	ppm	ASTM D5185(m)	>75	<b>17</b>	4	2
Potassium	ppm	ASTM D5185(m)	>20	<b>4</b>	<1	<1
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Silt	scalar	Visual*	NONE	<b>NONE</b>	NONE	VLITE
Debris	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG

Sodium	ppm	ASTM D5185(m)		<b>3</b>	0	0
Boron	ppm	ASTM D5185(m)	328	<b>175</b>	21	40
Barium	ppm	ASTM D5185(m)	1	<b>&lt;1</b>	<1	0
Molybdenum	ppm	ASTM D5185(m)		<b>0</b>	0	0
Manganese	ppm	ASTM D5185(m)		<b>3</b>	1	<1
Magnesium	ppm	ASTM D5185(m)	1	<b>3</b>	1	2
Calcium	ppm	ASTM D5185(m)	7	<b>7</b>	6	6
Phosphorus	ppm	ASTM D5185(m)	1145	<b>894</b>	458	531
Zinc	ppm	ASTM D5185(m)	3	<b>9</b>	7	6
Sulfur	ppm	ASTM D5185(m)	17909	<b>18764</b>	16696	17568
Visc @ 40°C	cSt	ASTM D7279(m)	99.6	<b>80.6</b>	75.7	79.9





**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : LH0288318  
**Lab Number** : 02635037  
**Unique Number** : 5776190  
**Test Package** : MOB 1

**Received** : 13 May 2024  
**Tested** : 13 May 2024  
**Diagnosed** : 13 May 2024 - Wes Davis

**Eacom Timber Corporation**  
 100 Old Nairn Centre Road  
 Nairn Centre, ON  
 CA P0M 2L0  
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.

T:  
F: