



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
KENWORTH 20-20
 Component
Diesel Engine
 Fluid
APRIL SUPERFLO SUPERPRO RXL SYN 5W40 (--- GAL)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		ASF0000387	ASF0000189	ASF0000341
Sample Date		Client Info		09 May 2024	16 Nov 2023	06 Aug 2023
Machine Age	hrs	Client Info		10684	9122	8613
Oil Age	hrs	Client Info		490	509	597
Filter Age	hrs	Client Info		490	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>100	13	22	25
Chromium	ppm	ASTM D5185(m)	>20	<1	<1	2
Nickel	ppm	ASTM D5185(m)	>4	0	<1	0
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>3	0	<1	<1
Aluminum	ppm	ASTM D5185(m)	>20	3	4	5
Lead	ppm	ASTM D5185(m)	>40	2	7	7
Copper	ppm	ASTM D5185(m)	>330	<1	1	1
Tin	ppm	ASTM D5185(m)	>15	0	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION












Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>25	2	4	8
Potassium	ppm	ASTM D5185(m)	>20	1	<1	4
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	ASTM D7844*	>3	0.2	0.3	0.4
Nitration	Abs/cm	ASTM D7624*	>20	11.1	11.8	12.7
Sulfation	Abs/.1mm	ASTM D7415*	>30	23.5	24.7	26.5
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

Le résultat pour le BN indique que la réserve d'alcalinité est acceptable pour l'huile. L'état de l'huile permet d'en prolonger l'utilisation.

Sodium	ppm	ASTM D5185(m)		4	4	7
Boron	ppm	ASTM D5185(m)		23	18	15
Barium	ppm	ASTM D5185(m)		0	<1	0
Molybdenum	ppm	ASTM D5185(m)		44	62	63
Manganese	ppm	ASTM D5185(m)		0	0	<1
Magnesium	ppm	ASTM D5185(m)		827	1090	1147
Calcium	ppm	ASTM D5185(m)		1262	910	943
Phosphorus	ppm	ASTM D5185(m)		993	996	1126
Zinc	ppm	ASTM D5185(m)		1202	1226	1274
Sulfur	ppm	ASTM D5185(m)		2717	2636	2748
Oxidation	Abs/.1mm	ASTM D7414*	>25	20.9	22.9	23.2
Base Number (BN)	mg KOH/g	ASTM D2896*		8.78	6.31	7.25
Visc @ 100°C	cSt	ASTM D7279(m)	14.2	12.8	12.7	12.6



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : ASF0000387 **Received** : 15 May 2024
Lab Number : 02635603 **Tested** : 16 May 2024
Unique Number : 5776756 **Diagnosed** : 16 May 2024 - Wes Davis
Test Package : MOB 2

April Super Flo
 9 rue Beland
 L'Isle-Verte, QC
 CA G0L 1K0
 Contact: Michel Jalbert
 mjalbert@aprilsuperflo.com
 T:
 F: (418)898-2192

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.