



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**833032**  
Component  
**Natural Gas Engine**  
Fluid  
**NOT GIVEN (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0118301</b>	GFL0111132	GFL0099477
Sample Date		Client Info		<b>15 May 2024</b>	24 Jan 2024	30 Oct 2023
Machine Age	kms	Client Info		<b>14042</b>	9334	5567
Oil Age	kms	Client Info		<b>0</b>	0	0
Filter Age	kms	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185(m)	>50	<b>11</b>	17	35
Chromium	ppm	ASTM D5185(m)	>4	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	1	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185(m)	>9	<b>1</b>	2	4
Lead	ppm	ASTM D5185(m)	>30	<b>0</b>	<1	1
Copper	ppm	ASTM D5185(m)	>35	<b>2</b>	3	19
Tin	ppm	ASTM D5185(m)	>4	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
White Metal	scalar	Visual*	NONE	<b>NONE</b>	---	---
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	---	---

**CONTAMINATION**











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>+100	<b>3</b>	6	34
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	1	<1
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Soot %	%	ASTM D7844*		<b>0</b>	0	0
Nitration	Abs/cm	ASTM D7624*	>20	<b>11.1</b>	10.8	8.8
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>22.5</b>	20.9	21.9
Silt	scalar	Visual*	NONE	<b>NONE</b>	---	---
Debris	scalar	Visual*	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	---	---
Appearance	scalar	Visual*	NORML	<b>NORML</b>	---	---
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<b>7</b>	6	4
Boron	ppm	ASTM D5185(m)		<b>8</b>	11	14
Barium	ppm	ASTM D5185(m)		<b>0</b>	0	3
Molybdenum	ppm	ASTM D5185(m)		<b>51</b>	55	115
Manganese	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	9
Magnesium	ppm	ASTM D5185(m)		<b>533</b>	564	712
Calcium	ppm	ASTM D5185(m)		<b>1535</b>	1497	1344
Phosphorus	ppm	ASTM D5185(m)		<b>624</b>	724	674
Zinc	ppm	ASTM D5185(m)		<b>865</b>	876	777
Sulfur	ppm	ASTM D5185(m)		<b>1913</b>	2121	2363
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>18.3</b>	17.2	16.6
Visc @ 100°C	cSt	ASTM D7279(m)		<b>14.5</b>	14.5	13.6



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0118301 **Received** : 17 May 2024  
**Lab Number** : 02636302 **Tested** : 17 May 2024  
**Unique Number** : 5785464 **Diagnosed** : 17 May 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: Visual )

**GFL Environmental - 225 - COT(D2)**  
 20 Brydon Drive  
 Etobicoke, ON  
 CA M9W 5R6  
 Contact: Rick Philip  
 rphilip@gflenv.com  
 T: (416)745-8080  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.