



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |



Machine Id
4530
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0112517 | GFL0112540 | GFL0102641 |
| Sample Date | | Client Info | | 16 May 2024 | 30 Mar 2024 | 08 Jan 2024 |
| Machine Age | hrs | Client Info | | 25513 | 25175 | 24630 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Changed | Changed | N/A |
| Filter Changed | | Client Info | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|----------|-----|---------------|------|--------------|----|----|
| Iron | ppm | ASTM D5185(m) | >80 | 10 | 21 | 5 |
| Chromium | ppm | ASTM D5185(m) | >5 | <1 | <1 | 0 |
| Nickel | ppm | ASTM D5185(m) | >2 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185(m) | >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185(m) | >30 | 2 | 7 | 2 |
| Lead | ppm | ASTM D5185(m) | >30 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185(m) | >150 | 2 | 4 | 1 |
| Tin | ppm | ASTM D5185(m) | >5 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |

CONTAMINATION











There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|---------------|------|----------------|------|------|
| Silicon | ppm | ASTM D5185(m) | >20 | 4 | 5 | 4 |
| Potassium | ppm | ASTM D5185(m) | >20 | <1 | <1 | <1 |
| Fuel | | WC Method | >5 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | ASTM D7844* | >3 | 0.2 | 0.2 | 0 |
| Nitration | Abs/cm | ASTM D7624* | >20 | 6.5 | 7.4 | 5.1 |
| Sulfation | Abs/.1mm | ASTM D7415* | >30 | 18.7 | 19.0 | 17.8 |
| Emulsified Water | scalar | Visual* | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|--------------|----------|---------------|-------|-------------|------|------|
| Sodium | ppm | ASTM D5185(m) | | 1 | 2 | 3 |
| Boron | ppm | ASTM D5185(m) | 2 | 2 | 3 | 6 |
| Barium | ppm | ASTM D5185(m) | 0 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185(m) | 50 | 54 | 58 | 57 |
| Manganese | ppm | ASTM D5185(m) | 0 | 0 | <1 | 0 |
| Magnesium | ppm | ASTM D5185(m) | 950 | 885 | 975 | 922 |
| Calcium | ppm | ASTM D5185(m) | 1050 | 970 | 1048 | 1037 |
| Phosphorus | ppm | ASTM D5185(m) | 995 | 897 | 989 | 982 |
| Zinc | ppm | ASTM D5185(m) | 1180 | 1084 | 1177 | 1128 |
| Sulfur | ppm | ASTM D5185(m) | 2600 | 2282 | 2492 | 2674 |
| Oxidation | Abs/.1mm | ASTM D7414* | >25 | 13.9 | 15.0 | 13.0 |
| Visc @ 100°C | cSt | ASTM D7279(m) | 12.00 | 11.5 | 11.7 | 11.3 |



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0112517
Lab Number : 02637132
Unique Number : 5786294
Test Package : MOB 1

GFL Environmental - 554 - Edmonton SW
 8409 - 15th Street NW
 Edmonton, AB
 CA T6P 0B8
 Contact: Tim Greig
 tgreig@gflenv.com
 T: (780)231-0521
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.