



VOLVO PENTA

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id

535110628

Component

Port Main Engine

Fluid

DIESEL ENGINE OIL SAE 15W40 (90 LTR)

RECOMMENDATION

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 15W40. Please confirm.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VPA053300	---	---
Sample Date		Client Info		13 May 2024	---	---
Machine Age	hrs	Client Info		17000	---	---
Oil Age	hrs	Client Info		500	---	---
Filter Age	hrs	Client Info		0	---	---
Oil Changed		Client Info		Changed	---	---
Filter Changed		Client Info		Changed	---	---
Sample Status				NORMAL	---	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>75	4	---	---
Chromium	ppm	ASTM D5185(m)	>8	0	---	---
Nickel	ppm	ASTM D5185(m)	>2	0	---	---
Titanium	ppm	ASTM D5185(m)	>3	0	---	---
Silver	ppm	ASTM D5185(m)	>2	0	---	---
Aluminum	ppm	ASTM D5185(m)	>15	<1	---	---
Lead	ppm	ASTM D5185(m)	>18	0	---	---
Copper	ppm	ASTM D5185(m)	>80	<1	---	---
Tin	ppm	ASTM D5185(m)	>14	0	---	---
Vanadium	ppm	ASTM D5185(m)		0	---	---

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>20	1	---	---
Potassium	ppm	ASTM D5185(m)	>20	1	---	---
Fuel		WC Method	>4.0	<1.0	---	---
Water		WC Method	>0.1	NEG	---	---
Glycol		WC Method		NEG	---	---
Soot %	%	ASTM D7844*		0.1	---	---
Nitration	Abs/cm	ASTM D7624*	>20	6.7	---	---
Sulfation	Abs/.1mm	ASTM D7415*	>30	17.3	---	---
Emulsified Water	scalar	Visual*	>0.1	NEG	---	---

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>158	1	---	---
Boron	ppm	ASTM D5185(m)	250	9	---	---
Barium	ppm	ASTM D5185(m)	10	0	---	---
Molybdenum	ppm	ASTM D5185(m)	100	1	---	---
Manganese	ppm	ASTM D5185(m)		0	---	---
Magnesium	ppm	ASTM D5185(m)	450	119	---	---
Calcium	ppm	ASTM D5185(m)	3000	2219	---	---
Phosphorus	ppm	ASTM D5185(m)	1150	836	---	---
Zinc	ppm	ASTM D5185(m)	1350	1044	---	---
Sulfur	ppm	ASTM D5185(m)	4250	2934	---	---
Oxidation	Abs/.1mm	ASTM D7414*	>25	9.8	---	---
Visc @ 40°C	cSt	ASTM D7279(m)	115	87.9	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	14.4	12.7	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	126	141	---	---



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : VPA053300 **Received** : 23 May 2024
Lab Number : 02637232 **Tested** : 23 May 2024
Unique Number : 5786394 **Diagnosed** : 23 May 2024 - Kevin Marson
Test Package : MOB 1 (Additional Tests: KV40, VI)

MERCURY TRANSPORT
 6695 NELSON AVE
 WEST VANCOUVER, BC
 CA V7W 2B2
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
 F: