Machine Id


## Wakefield SAE 50 GL4

ASTM D92 - Open-Cup Flash Point = 232°C.

**Unknown Component** 

{not provided} (--- GAL)

RECOMMENDATION		Test	UOM	Method	Limit/Abn	Current	History1	History2
This is a baseline read-out on the submit	tted sample.	Sample Number		Client Info		PP		
		Sample Date		Client Info		22 May 2024		
		Machine Age	hrs	Client Info		0		
		Oil Age	hrs	Client Info		0		
		Filter Age	hrs	Client Info		0		
		Oil Changed		Client Info		N/A		
		Filter Changed		Client Info		N/A		
		Sample Status				NORMAL		
WEAR		White Metal	scalar	Visual*	NONE	NONE		
{not applicable}		Yellow Metal	scalar	Visual*	NONE	NONE		
CONTAMINATION		Water		WC Method		NEG		
{not applicable}		Silt	scalar	Visual*	NONE	NONE		
		Debris	scalar	Visual*	NONE	NONE		
		Sand/Dirt	scalar	Visual*	NONE	NONE		
		Appearance	scalar	Visual*	NORML	NORML		
		Odor	scalar	Visual*	NORML	NORML		
FLUID CONDITION		COC Flash Point	°C	ASTM D92*		232		





**CALA** ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : PP Lab Number : 02637320

Unique Number : 5786482 Test Package: TEST (Additional Tests: COC Flash)

**Tested** Diagnosed

Received : 23 May 2024

: 24 May 2024

: 24 May 2024 - Kevin Marson

Contact: Tony Fallico tfallico@wakefieldcanada.ca

WAKEFIELD CANADA INC.

3620 LAKESHORE BLVD WEST

T: (416)252-5511 F:

TORONTO, ON

CA M8W 1P2

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.