



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**1951**  
 Component  
**Diesel Engine**  
 Fluid  
**DIESEL ENGINE OIL SAE 15W40 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0932491</b>	WC0925697	WC0883004
Sample Date		Client Info		<b>15 May 2024</b>	03 Apr 2024	01 Feb 2024
Machine Age	hrs	Client Info		<b>17046</b>	16537	15855
Oil Age	hrs	Client Info		<b>509</b>	542	500
Filter Age	hrs	Client Info		<b>509</b>	542	500
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>N/A</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>100	<b>10</b>	14	10
Chromium	ppm	ASTM D5185(m)	>20	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185(m)	>4	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>20	<b>1</b>	1	2
Lead	ppm	ASTM D5185(m)	>40	<b>0</b>	0	<1
Copper	ppm	ASTM D5185(m)	>330	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185(m)	>15	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0

## CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>25	<b>2</b>	2	3
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0	<1
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	ASTM D7844*	>3	<b>0.2</b>	0.4	0.2
Nitration	Abs/cm	ASTM D7624*	>20	<b>8.8</b>	9.8	8.7
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>23.1</b>	21.9	21.1
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>158	<b>1</b>	1	1
Boron	ppm	ASTM D5185(m)	250	<b>2</b>	2	1
Barium	ppm	ASTM D5185(m)	10	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185(m)	100	<b>59</b>	60	58
Manganese	ppm	ASTM D5185(m)		<b>0</b>	0	0
Magnesium	ppm	ASTM D5185(m)	450	<b>969</b>	981	959
Calcium	ppm	ASTM D5185(m)	3000	<b>1057</b>	1061	1075
Phosphorus	ppm	ASTM D5185(m)	1150	<b>996</b>	994	1011
Zinc	ppm	ASTM D5185(m)	1350	<b>1213</b>	1197	1186
Sulfur	ppm	ASTM D5185(m)	4250	<b>2506</b>	2436	2720
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>22.5</b>	20.7	18.9
Visc @ 100°C	cSt	ASTM D7279(m)	14.4	<b>14.1</b>	14.1	14.1



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0932491  
**Lab Number** : 02637642  
**Unique Number** : 5786804  
**Test Package** : MOB 1  
**Received** : 27 May 2024  
**Tested** : 27 May 2024  
**Diagnosed** : 27 May 2024 - Wes Davis

**KINGSTON TRANSIT**  
 1181 JOHN COUNTER BLVD  
 KINGSTON, ON  
 CA K7K 6C7  
 Contact: Brent Gunter  
 bgunter@cityofkingston.ca  
 T: (613)546-4291  
 F: (613)542-1504

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.