



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Area

[1282438]

Machine Id

514002

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0118533 | GFL0110672 | GFL0110701 |
| Sample Date | | Client Info | | 24 May 2024 | 26 Mar 2024 | 18 Jan 2024 |
| Machine Age | hrs | Client Info | | 30247 | 29738 | 29242 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | N/A | Changed |
| Filter Changed | | Client Info | | N/A | N/A | Changed |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|----------|-----|---------------|------|--------------|----|----|
| Iron | ppm | ASTM D5185(m) | >165 | 6 | 6 | 8 |
| Chromium | ppm | ASTM D5185(m) | >5 | 0 | 0 | <1 |
| Nickel | ppm | ASTM D5185(m) | >4 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185(m) | >2 | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185(m) | >2 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185(m) | >20 | <1 | 1 | 2 |
| Lead | ppm | ASTM D5185(m) | >150 | <1 | <1 | 1 |
| Copper | ppm | ASTM D5185(m) | >90 | <1 | <1 | <1 |
| Tin | ppm | ASTM D5185(m) | >5 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185(m) | | 0 | 0 | 0 |

CONTAMINATION











There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|---------------|------|----------------|------|------|
| Silicon | ppm | ASTM D5185(m) | >35 | 1 | 2 | 3 |
| Potassium | ppm | ASTM D5185(m) | >20 | <1 | <1 | 1 |
| Fuel | | WC Method | >3.0 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | ASTM D7844* | >7.5 | 0.1 | 0.1 | 0.2 |
| Nitration | Abs/cm | ASTM D7624* | >20 | 7.0 | 6.5 | 6.8 |
| Sulfation | Abs/.1mm | ASTM D7415* | >30 | 18.7 | 18.3 | 18.6 |
| Emulsified Water | scalar | Visual* | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|--------------|----------|---------------|------|-------------|------|------|
| Sodium | ppm | ASTM D5185(m) | | 5 | 3 | 3 |
| Boron | ppm | ASTM D5185(m) | 0 | 2 | 3 | 1 |
| Barium | ppm | ASTM D5185(m) | 0 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185(m) | 60 | 58 | 59 | 59 |
| Manganese | ppm | ASTM D5185(m) | 0 | 0 | 0 | 0 |
| Magnesium | ppm | ASTM D5185(m) | 1010 | 964 | 985 | 968 |
| Calcium | ppm | ASTM D5185(m) | 1070 | 1037 | 1044 | 1095 |
| Phosphorus | ppm | ASTM D5185(m) | 1150 | 990 | 1002 | 1010 |
| Zinc | ppm | ASTM D5185(m) | 1270 | 1183 | 1190 | 1190 |
| Sulfur | ppm | ASTM D5185(m) | 2060 | 2527 | 2570 | 2730 |
| Oxidation | Abs/.1mm | ASTM D7414* | >25 | 13.8 | 13.7 | 13.8 |
| Visc @ 100°C | cSt | ASTM D7279(m) | 15.4 | 13.8 | 13.6 | 13.5 |



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0118533
Lab Number : 02637861
Unique Number : 5787023
Test Package : MOB 1

GFL Environmental - 207 - Pickering SW
 1034 TOY AVENUE, PICKERING YARD
 PICKERING, ON
 CA L1W 3P1
 Contact: Ian Patton
 ipatton@gflenv.com
 T: (905)831-6297
 F: (905)426-3577

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.