



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
120280-1216

Component
Front Right Wheel Hub

Fluid
PETRO CANADA TRAXON 75W90 SYNTHETIC (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0288343	LH0276854	LH0186035
Sample Date		Client Info		15 May 2024	03 Nov 2023	05 May 2022
Machine Age	hrs	Client Info		9095	8000	5066
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		None	None	None
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>325	3	54	121
Chromium	ppm	ASTM D5185(m)	>3	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	0	<1	<1
Titanium	ppm	ASTM D5185(m)	>4	0	0	0
Silver	ppm	ASTM D5185(m)	>2	0	0	0
Aluminum	ppm	ASTM D5185(m)	>10	<1	2	2
Lead	ppm	ASTM D5185(m)	>3	0	<1	0
Copper	ppm	ASTM D5185(m)	>70	25	12	6
Tin	ppm	ASTM D5185(m)	>2	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	VLITE	LIGHT
Yellow Metal	scalar	Visual*	NONE	VLITE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>70	1	32	41
Potassium	ppm	ASTM D5185(m)	>20	<1	1	<1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	VLITE	VLITE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<1	2	3
Boron	ppm	ASTM D5185(m)	328	309	220	141
Barium	ppm	ASTM D5185(m)	1	0	0	0
Molybdenum	ppm	ASTM D5185(m)		0	0	0
Manganese	ppm	ASTM D5185(m)		<1	<1	1
Magnesium	ppm	ASTM D5185(m)	1	3	2	1
Calcium	ppm	ASTM D5185(m)	7	15	56	50
Phosphorus	ppm	ASTM D5185(m)	1145	1255	1154	1332
Zinc	ppm	ASTM D5185(m)	3	27	152	117
Sulfur	ppm	ASTM D5185(m)	17909	20153	17841	17583
Visc @ 40°C	cSt	ASTM D7279(m)	99.6	103	86.5	83.8



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : LH0288343 **Received** : 29 May 2024
Lab Number : 02638605 **Tested** : 30 May 2024
Unique Number : 5787767 **Diagnosed** : 30 May 2024 - Wes Davis
Test Package : MOB 1

American Iron and Metal
 1273 Kelly Lake Rd.
 Sudbury, ON
 CA P3E 5P5
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: