WEAR CONTAMINATION FLUID CONDITION **NORMAL NORMAL NORMAL**

TTC - SURFACE [86175]

1900 YONGE ST TORONTO TTC - SURFACE W.C. MCBRIEN BLDG

Right Diesel Engine

RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
Resample at the next service interval to monitor.	Sample Number		Client Info		PN0006335		
	Sample Date		Client Info		26 May 2024		
	Machine Age	hrs	Client Info		306		
	Oil Age	hrs	Client Info		13		
	Filter Age	hrs	Client Info		13		
	Oil Changed		Client Info		Changed		
	Filter Changed		Client Info		Changed		
	Sample Status				NORMAL		
VEAR	Iron	ppm	ASTM D5185(m)	\120	1		
WEAT	Chromium	ppm	ASTM D5185(m)		0		
Metal levels are typical for a new component breaking in.	Nickel	ppm	ASTM D5185(m)		0		
	Titanium	ppm	ASTM D5185(m)		0		
	Silver	ppm	ASTM D5185(m)	>5	0		
	Aluminum	ppm	ASTM D5185(m)		<1		
	Lead	ppm	ASTM D5185(m)		0		
	Copper	ppm	ASTM D5185(m)		<1		
	Tin	ppm	ASTM D5185(m)	>10	0		
	Vanadium	ppm	ASTM D5185(m)		0		
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
ONTAMINATION	Silicon	nnm	ASTM D5185(m)	> 25	<1		
ONTAMINATION	Potassium	ppm	ASTM D5185(m)		1		
There is no indication of any contamination in the oil.	Fuel	ppiii	WC Method		<1.0		
	Water		WC Method		NEG		
	Glycol		WC Method	<i>></i> 0.1	NEG		
	Soot %	%	ASTM D7844*		0		
	Nitration	Abs/cm	ASTM D7624*	>20	5.2		
	Sulfation	Abs/.1mm		>30	15.0		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.1	NEG		
LUID CONDITION	O- 45		ACTM DE10F()	100			
LUID CONDITION	Sodium Boron	ppm	ASTM D5185(m) ASTM D5185(m)	>192	1		
The condition of the oil is acceptable for the time in service.		ppm	. ,		3		
	Barium Molybdenum	ppm	ASTM D5185(m) ASTM D5185(m)		0		
	Manganese	ppm			0		
	Magnesium	ppm	ASTM D5185(m) ASTM D5185(m)		0 13		
	Calcium	ppm	ASTM D5185(III) ASTM D5185(m)	3780	2157		
	Phosphorus	ppm	ASTM D5185(m) ASTM D5185(m)		808		
	Zinc	ppm	ASTM D5185(III) ASTM D5185(m)	1500	917		
	Sulfur	ppm	ASTM D5185(m)	3800	2843		
	Oxidation	Abs/.1mm	ASTM D3163(III) ASTM D7414*		8.8		
	Visc @ 100°C	cSt	ASTM D7279(m)		13.7		





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : PN0006335

Lab Number : 02639587 Unique Number : 5788749

Diagnosed Test Package : MOB 1 (Additional Tests: Visual) To discuss this sample report, contact Customer Service at 1-800-268-2131.

Received

Tested

: 04 Jun 2024

: 05 Jun 2024

: 05 Jun 2024 - Wes Davis

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

POWER STATION INC.

1050 JAYSON COURT MISSISSAUGA, ON CA L4W 2V5 Contact: Brett Kinkley Bkinkley@pwrstn.com

F: (905)565-8544